

TYPE OF HOUSE: (DOYL-201)  
PLAN #: NORTHWOOD  
ELEVATION:E, 8' BSMT  
GARAGE:1 CAR FRONT LEFT  
FRONT BRICK/STONE TO  
GRADE, FULL BSMT BATH,  
WINDOWS IN BSMT (2),  
EGRESS WINDOWS (2),  
16'x12' DECK, 5' LEAD  
WALK FROM DRIVE TO  
FRONT DOOR, 1 CAR GAR

I CERTIFY THAT THIS PLAN WAS PREPARED  
BY ME AND IS CORRECT TO THE BEST OF  
MY KNOWLEDGE AND BELIEF

12-1-2025  
STAN R. LOCH P.F. #63332 DATE



ZONING: SINGLE FAMILY RESIDENTIAL DISTRICT (A)  
FRONT YARD SETBACK: 25'  
CORNER SIDE YARD: 15'  
SIDE YARD: 5'  
REAR YARD: 30'  
\*SEE CODE SECTION 1121.08

HORIZ. SCALE: 1"=20'		VERT. SCALE:	5425 WA VALLEY <b>440-</b>
DRAWN BY: JDC		DATE: 10-20-2025	
CHECKED BY: SRL		DRAWING NO.: 20244047	
JOB NO.: 20244047		SHEET: 1 OF 2	

5425 WARNER ROAD - SUITE 12  
VALLEY VIEW, OHIO 44125  
419-693-8271

■ 2000-2001

SITE PLAN FOR  
DREES HOMES  
DOYL 201  
3756 BENDEMEER ROAD  
SUBLOT 96 OF THE  
AYLOR MAYFIELD CO'S SEVERN  
PARK ALLOT. VOL. 97 PG. 20  
CITY OF CLEVELAND HEIGHTS  
CUYAHOGA COUNTY  
STATE OF OHIO

WEST PROPERTY LINE DETAILEAST PROPERTY LINE DETAIL

**LOT COVERAGE:**  
CONCRETE = 672 SQ.FT.  
HOUSE = 2,317 SQ.FT.  
TOTAL = 6,123 SQ.FT

**NOTE:**  
EXISTING SANITARY LATERAL,  
AND STORM LATERAL ARE  
ASSUMED. CONNECTIONS TO  
BE FIELD VERIFIED BEFORE  
BEGINNING CONSTRUCTION.

**NOTE:**  
SUMP PUMP AND/OR  
GRINDER PUMP MAY  
BE NEEDED. LATERALS MUST BE  
VERIFIED PRIOR TO  
ANY CONSTRUCTION.

① = EX WAT CONN  
② = EX SAS LAT (ASSUMED LOCATION)  
③ = EX STS LAT (ASSUMED LOCATION)  
④ = PROP 1" TYPE 'K' COPPER WAT CONN  
⑤ = PROP 6" SDR 35 PVC SAS @ 1% MIN  
⑥ = PROP 6" SDR 35 PVC STS @ 1% MIN  
⑦ = 10' OF EX CONC SIDEWALK TO BE  
REMOVED AND REPLACED

**LATERAL NOTE**  
CONTRACTOR TO  
TELESCOPE EXISTING  
LATERALS TO VERIFY  
LOCATION AND  
DEPTHS OF SANITARY  
AND STORM  
CONNECTIONS

LEGEND	
○	= IRON PIN FND
●	= IRON PIN SET 5/8"X30" REBAR CAPPED "AZTECH 8249"
◎	= SANITARY MANHOLE
◎	= STORM MANHOLE
○	= FIRE HYDRANT
○	= POWER POLE
○	= TREE
AC	= AC UNIT
△	= OFFSET HUB
○○○	= SILT FENCE/FILTER SOCK
←	= FLOW DIRECTION
→	= SWALE
—	= EXISTING GRADE
—	= PROPOSED GRADE
○○	= BUSH
W	= WATER MARK
●	= PROP CLEANOUT

BUILDER: DREES HOMES  
CLEVELAND DIVISION  
6860 W. SNOWVILLE ROAD  
SUITE 105 BRECKSVILLE, OH 44141  
PHONE: 440-746-6426

**REFERENCES:**  
NORTH WOODLAND ROAD WIDENING PLAT  
VOL.97 PG.21  
BY: F.A. PEASE ENGINEERING CO.  
DATED: APRIL 1926  
TAYLOR MAYFIELD CO'S SEVERN PARK ALLOT.  
VOL.97 PG.20  
BY: F.A. PEASE ENGINEERING CO.  
DATED: APRIL 1926

HORIZ. SCALE: 1"=20'	VERT. SCALE:
DRAWN BY: JDC	DATE: 10-20-2025
CHECKED BY: SRL	DRAWING NO.: 20244047
JOB NO.: 20244047	SHEET: 2 OF 2

5425 WARNER ROAD - SUITE 12  
VALLEY VIEW, OHIO 44125  
440-602-9071 FAX 216-369-0259  
**AZTECH**  
ENGINEERING + SURVEYING  
Civil Engineering + Land Surveying

SITE PLAN FOR  
DREES HOMES  
DOYL 201  
3756 BENDMEER ROAD  
SUBLOT 96 OF THE  
TAYLOR MAYFIELD CO'S SEVERN  
PARK ALLOT. VOL.97 PG.20  
CITY OF CLEVELAND HEIGHTS  
CUYAHOGA COUNTY  
STATE OF OHIO

1	12/25	LOT COVERAGE	JC
NO.	DATE	DESCRIPTION	BY



Square Footage		Division: Cleveland																																																				
FINISHED LOWER LEVEL (NET)	1151	Building Code: 2019 Residential Code of Ohio																																																				
FIRST FLOOR (NET)	1961	Index to the Drawings																																																				
SECOND FLOOR (GROSS)	2024	<table border="1"> <thead> <tr> <th>Sheet No.</th><th>Sheet Name</th></tr> </thead> <tbody> <tr> <td>OC.1</td><td>Cover Sheet</td></tr> <tr> <td>ON.1</td><td>General Notes</td></tr> <tr> <td>1.01</td><td>Foundation Plan</td></tr> <tr> <td>1.02</td><td>Basement Framing Plan</td></tr> <tr> <td>1.03</td><td>Basement Mechanical Plan</td></tr> <tr> <td>2.01F</td><td>First Floor Framing Plan</td></tr> <tr> <td>2.01S</td><td>First Floor Structural Plan</td></tr> <tr> <td>2.02F</td><td>Second Floor Framing Plan</td></tr> <tr> <td>2.02S</td><td>Second Floor Structural Plan</td></tr> <tr> <td>3.01</td><td>Roof Plan</td></tr> <tr> <td>3.02</td><td>First Floor Subfloor Plan</td></tr> <tr> <td>4.01</td><td>Second Floor Subfloor Plan</td></tr> <tr> <td>4.02</td><td>First Floor Mechanical Plan</td></tr> <tr> <td>5.01</td><td>Second Floor Mechanical Plan</td></tr> <tr> <td>5.02</td><td>Building Section</td></tr> <tr> <td>6.01</td><td>Building Section</td></tr> <tr> <td>6.02</td><td>Front Elevation</td></tr> <tr> <td>6.03</td><td>Garage Side Elevation</td></tr> <tr> <td>6.04</td><td>Rear Elevation</td></tr> <tr> <td>7.01</td><td>Side Elevation</td></tr> <tr> <td>7.02</td><td>House Specific Details</td></tr> <tr> <td>7.03</td><td>House Specific Details</td></tr> <tr> <td>7.04</td><td>House Specific Details</td></tr> <tr> <td>S-0</td><td>Structural Notes</td></tr> <tr> <td>SD-1</td><td>Lateral Details</td></tr> </tbody> </table>	Sheet No.	Sheet Name	OC.1	Cover Sheet	ON.1	General Notes	1.01	Foundation Plan	1.02	Basement Framing Plan	1.03	Basement Mechanical Plan	2.01F	First Floor Framing Plan	2.01S	First Floor Structural Plan	2.02F	Second Floor Framing Plan	2.02S	Second Floor Structural Plan	3.01	Roof Plan	3.02	First Floor Subfloor Plan	4.01	Second Floor Subfloor Plan	4.02	First Floor Mechanical Plan	5.01	Second Floor Mechanical Plan	5.02	Building Section	6.01	Building Section	6.02	Front Elevation	6.03	Garage Side Elevation	6.04	Rear Elevation	7.01	Side Elevation	7.02	House Specific Details	7.03	House Specific Details	7.04	House Specific Details	S-0	Structural Notes	SD-1	Lateral Details
Sheet No.	Sheet Name																																																					
OC.1	Cover Sheet																																																					
ON.1	General Notes																																																					
1.01	Foundation Plan																																																					
1.02	Basement Framing Plan																																																					
1.03	Basement Mechanical Plan																																																					
2.01F	First Floor Framing Plan																																																					
2.01S	First Floor Structural Plan																																																					
2.02F	Second Floor Framing Plan																																																					
2.02S	Second Floor Structural Plan																																																					
3.01	Roof Plan																																																					
3.02	First Floor Subfloor Plan																																																					
4.01	Second Floor Subfloor Plan																																																					
4.02	First Floor Mechanical Plan																																																					
5.01	Second Floor Mechanical Plan																																																					
5.02	Building Section																																																					
6.01	Building Section																																																					
6.02	Front Elevation																																																					
6.03	Garage Side Elevation																																																					
6.04	Rear Elevation																																																					
7.01	Side Elevation																																																					
7.02	House Specific Details																																																					
7.03	House Specific Details																																																					
7.04	House Specific Details																																																					
S-0	Structural Notes																																																					
SD-1	Lateral Details																																																					
- VOLUME SPACE (GROSS)	0																																																					
SECOND FLOOR (NET)	2024																																																					
TOTAL LIVING (NET)	5136																																																					
UNFINISHED BASEMENT	836																																																					
UNFINISHED ATTIC STORAGE	0																																																					
GARAGE	213																																																					
COVERED FRONT PORCH	137																																																					
COVERED REAR PATIO	0																																																					
REAR DECK	225																																																					

PER ANSI Z765-2003

### Redraws

Plan Review: 10/10/25

ADD ENGINEERING AND DETAILS

RESIDENCE FOR:  
**KLEINMAN**  
3756 BENDMEER  
ELEVATE

Job Number: DOYL-0201-00	Drawing Date: 09/24/25	Coord Name: LUKE R.	Coord Phone: 859.578.4212
-----------------------------	---------------------------	------------------------	------------------------------

House Name:	Drawn By: MRPH
-------------	-------------------

Series:

Plan No.:

the NORTHWOOD

<b>drees</b> HOMES <sup>SM</sup>	Sheet Information	<b>OC.1</b>
-------------------------------------	-------------------	-------------

6860 WEST SNOWVILLE ROAD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Architecture Plan Review:  No Comments  See Comments Items drawn on any drawings and not written in the contract selections **WILL NOT** be included in the site specific drawings.

Customer Plan Review Signature

Customer Request:	Design Solution:	Reason For Modification:	Comments:	I understand that my new Drees home will be built in general conformance to the plans, specifications, selections and the Purchase Agreement, all of which I have reviewed and approved. This set of plans may not reflect the elevations or options for my house. Drees draws the standard plans complete with the most common options. The subcontractor's sets will show only the options I selected in my selection sheets. I have reviewed the plot plan for my house and understand that there may be some field adjustments as to the exact location of the house on the lot. I further understand that my home will not be built exactly like any other Drees home or Model and that some minor variations from my plans and specifications may occur since every home that is built has its own set of unique construction problems that must be dealt with as the home is being built.  Customer: _____ Date: _____ Customer: _____ Date: _____
1. SINK ROUGH-IN PER LOCATION	1. NOT SHOWN	1. NOTED TO BE PLACED AT DESIGN CENTER IN PAPERWORK	1. XXXXX	
2. XXXXX	2. XXXXX	2. XXXXX	2. XXXXX	
3. XXXXX	3. XXXXX	3. XXXXX	3. XXXXX	
4. XXXXX	4. XXXXX	4. XXXXX	4. XXXXX	

## GENERAL NOTES - CLEVELAND

### FOUNDATION NOTES

- ALL FOUNDATION WALLS TO BE 8" THICK Poured CONCRETE UNLESS OTHERWISE NOTED.
- PROVIDE FOOTER DRAIN TILE ON OUTSIDE OF FOOTER TO SUMP PUMP OR TO DAYLIGHT.
- BASEMENT WINDOW LOCATIONS MAY VARY FROM DRAWING DUE TO LOT CONDITIONS.
- BACKFILL ADJACENT TO FOUNDATION WALLS SHALL NOT BE PLACED UNTIL THE WALL HAS SUFFICIENT STRENGTH AND HAS BEEN ANCHORED TO THE FLOOR OR HAS BEEN SUFFICIENTLY BRACED TO PREVENT DAMAGE BY THE BACKFILL.
- WATERPROOF FOUNDATION WITH POLY MODIFIED ASPHALT SPRAY.
- ASSUMED ALLOWABLE SOIL BEARING PRESSURE - 2,000 PSF
- PROVIDE FOOTER DRAIN CLEANOUT 10' FROM BACK CORNER ON SIDE OF HOUSE OPPOSITE THE GARAGE.
- EXTERIOR FLATWORK AND GARAGE SLABS SHALL BE POURED WITH A MINIMUM CONCRETE STRENGTH OF 4,500 LBS.
- VERTICAL CONTROL JOINTS IN BASEMENT FOUNDATION WALLS - STANDARD LOCATION GUIDELINES:
  - 1) PLACE A CONTROL JOINT IN ALL UNBRACED WALLS OVER 30' IN LENGTH. (NOTE: 'T' WALLS AND CORNERS COUNT AS A BRACE).
  - 2) WINDOWS THAT ARE LARGER THAN THE STANDARD BASEMENT WINDOW REQUIRE A CONTROL JOINT.
  - 3) CONTROL JOINTS ARE NOT REQUIRED AT EVERY WINDOW THAT IS STANDARD SIZE.
- IF THERE IS A STANDARD WINDOW LOCATED IN A WALL SEGMENT THAT REQUIRES A CONTROL JOINT, THEN THE CONTROL JOINT SHOULD BE PLACED ON THE SIDE OF THE WINDOW THAT IS ADJACENT TO THE LONG SIDE OF THE WALL. IF THERE IS MORE THAN ONE WINDOW IN A WALL THEN ONLY ONE WINDOW SHOULD HAVE A CONTROL JOINT.
- DOORS DO NOT GET CONTROL JOINTS.
- CONTROL JOINTS SHOULD NOT BE LOCATED WITHIN 3' OF A BEAM POCKET.
- CONTROL JOINTS ARE REQUIRED AT THE FIRST AND LAST STEP DOWN AT STEPPED BASEMENT FOUNDATION WALLS.
- OVERALL FOUNDATION WALL HEIGHT MAY VARY UP TO 1".
- GARAGE AND BASEMENT SLABS TO HAVE A MINIMUM 6 MIL. VAPOR BARRIER BETWEEN GRAVEL AND SLAB.
- INTERIOR FLATWORK SHALL HAVE A MINIMUM CONCRETE STRENGTH OF 3,000 PSI.
- PLACE GARAGE SLAB CONTROL JOINTS PERPENDICULAR TO ONE ANOTHER, EACH STARTING FROM THE CENTERLINE OF GARAGE WALL. WHEN OVERDIG EXCEEDS 2'-0", SLAB CONTROL JOINTS SHOULD BE OFFSET FROM PILASTER 2'-0" WITH ANOTHER JOINT RUNNING PERPENDICULAR.
- ALL VERTICAL STEEL AND ALL STEEL IN STRUCTURAL SLABS TO BE GRADE 60. ALL HORIZONTAL STEEL IN FOUNDATION WALLS AND FOOTERS TO BE GRADE 40 STEEL.

### FRAMING NOTES

DESIGN LOADS:  
 FLOORS: 40 psf LIVE LOAD + 10 psf DEAD LOAD = 50 psf GARAGE FLOOR: 50 psf LIVE LOAD SEISMIC: "A" & "B"  
 ROOF: 25 psf LIVE LOAD + 20 psf DEAD LOAD = 45 psf WIND SPEED: 115 MPH

DESIGN DEFLECTION LIMITS (BASED ON LIVE LOAD, EXCEPT MASONRY):  
 RAFTERS GREATER THAN 3:12 L/180 CEILINGS L/240

ASCMRY VENEER L/600

NOMINAL LUMBER FLOORS: L/360

MANUFACTURED WOOD FLOORS: DESIGNED TO MINIMUM PRO RATING OF 38 (OR EQUIVALENT)\*

NO MORE THAN 8 POINT DIFFERENCE BETWEEN ADJACENT SPANS.

\* IF PRO-RATING EQUIVALENCY CANNOT BE EVALUATED, ADHERE TO THE FOLLOWING MINIMUMS:

- L/480 [LIVE LOAD] FOR SPANS UP TO 16'-0" AND NO GREATER THAN 1/2" DEFLECTION
- L/600 [LIVE LOAD] FOR SPANS OVER 16'-0" IF SIMPLE SPAN; L/840 FOR SPANS OVER 16'-0" IF CONTINUOUS SPAN. NO GREATER THAN 1/2" DEFLECTION

- JOIST SPACING: 19.2" o.c. MAXIMUM SPACING

DOUBLE EVERY OTHER FLOOR JOIST UNDER KITCHEN ISLANDS

INSTALL UNCOUPLING MEMBRANE IN TILE FLOOR AREAS IF 19.2" o.c. FLOOR JOIST SPACING

GLUE AND MECHANICALLY FASTEN [SCREWS] WOOD FLOOR IF 19.2" o.c. FLOOR JOIST SPACING

- MANUFACTURED WOOD PRODUCTS (INCLUDING, BUT NOT LIMITED TO, STRUCTURAL WOOD BEAMS AND I-JOISTS) SHALL BE FABRICATED, HANDLED, AND INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. PROVIDE I-JOIST PROTECTION AS REQUIRED BY 2019 RCO SECTION 302.13.

- JOISTS ARE NOT TO BE PLACED DIRECTLY OVER INTERIOR PARALLEL WALLS. (TO PREVENT UNEVEN FLOOR DEFLECTION FROM OCCURRING)

- ALL WOOD BEAMS/HEADERS: 2x6 TO BE SPF STUD GRADE OR BETTER

2x8 OR LARGER TO BE NORTHERN HEM FIR #2 KD WITH E-1,400,000 p.s.i.

- ALL WOOD JOISTS TO BE S. PINE #2 KD WITH E-1,700,000 p.s.i., SPAN MUST BE LESS THAN 20', USE HEM FIR IF SPAN IS 20' OR MORE.

- ALL LVL's TO BE TJM MICROLAM WITH Fb=2600, Fv=285, MOE=1.9, Fc=750.

- ALL STEEL BEAMS TO HAVE A 2x6 TOP PLATE.

- ALL STEEL COLUMNS TO BE 3-1/2" IN DIAMETER AND ADJUSTABLE, UNLESS OTHERWISE NOTED.

-- EXTERIOR WALL TO BE 2x4 SPF STUD GRADE AT 16" O.C. UNLESS OTHERWISE NOTED (WALL HEIGHTS 10'-0"+, SIZES WILL BE NOTED PER PRINTS)

- ALL INTERIOR BEARING WALLS AND WALLS AT BASEMENT & FIRST FLOOR STAIRWELLS, KITCHEN, AND GARAGE TO BE 2x4 SPF STUD GRADE AT 16" O.C.; ALL OTHER NON-BEARING INTERIOR WALLS TO BE 2x4 SPF STUD GRADE AT 24" O.C. UNLESS OTHERWISE NOTED.

- ALL WALLS TO BE 3 1/2" UNLESS OTHERWISE NOTED.

- PROVIDE 4-1/2" SOLID BEARING TO FOUNDATION OR BEAM BELOW FOR ALL BEAMS, HEADERS, AND GIRDER TRUSSES. PROVIDE BLOCKING BETWEEN JOISTS AS REQUIRED.

- CHECK SELECTIONS FOR FLOOR COVERINGS AT TOP AND BOTTOM OF STAIR RISERS AND ADJUST RISER HEIGHT AS NEEDED.

- SEE FIREPLACE ELEVATION DETAIL FOR ADDITIONAL FRAMING REQUIREMENTS, IF ANY, AND SEE SELECTION SHEET FOR SIZE AND STYLE OF FIREPLACE.

- PROVIDE BLOCKING AT ALL HANDRAIL BRACKETS, TOWEL BARS AND TOILET PAPER HOLDER LOCATIONS.

- PROVIDE 20 MIN. FIRE-RATED DOOR AT GARAGE/HOUSE ENTRY.

- PAD OUT GARAGE WALL CAVITIES/ FLOOR JOIST CAVITIES 3-1/2" TO RECEIVE FULL BATT INSULATION IF HEATING/ PLUMBING ARE PRESENT. FRAMING FOR HVAC CHASE TO EXTEND DOWN TO GARAGE SLAB.

- ALL BEARING WALLS TO HAVE DOUBLE TOP PLATE.

- A PARTIALLY EXPOSED EXTERIOR WALL, WALL SHEATHING SHOULD CONTINUOUSLY RUN TO BOTTOM OF SUB FLOOR.

- ALL LUMBER CONTACTING CONCRETE TO BE PRESSURE TREATED.

- ALL FASTENERS, HANGERS, AND OTHER CONNECTORS TO BE USED WITH PRESSURE TREATED WOOD ARE TO HAVE ZMAX COATING (OR EQUIVALENT) HOT-DIPPED GALVANIZED OR STAINLESS STEEL.

- STAIR NOSING SHOULD BE 3/4" TO 1-1/4" MAX. STAIR TREADS ARE DIMENSIONED FROM NOSING TO NOSING, WITH A 9" MIN. TREAD.

- ALL EXTERIOR WALLS AND INTERIOR BEARING WALLS, FRAMED HIGHER THAN THE STD PLATE HEIGHT, SHALL BE FRAMED WITH CONTINUOUS FULL HEIGHT STUDS TO THE HIGHEST CEILING (I.E. NO INTERMEDIATE BREAKS) TO PREVENT LATERAL HINGE CONDITIONS.

- 5/8" (MIN.) OSB TO BE INSTALLED ON PORCH CEILINGS WHEN LIVING SPACE IS ABOVE.

- ALL EGRESS WINDOWS TO HAVE MINIMUM OPENING DIMENSIONS OF 24" IN HEIGHT, 20" IN WIDTH, AND HAVE A MINIMUM OPENING AREA OF 5.7 S.F. - ALL EGRESS WINDOWS TO BE A MAXIMUM OF 44" OFF OF FINISHED FLOOR.

### FRAMING NOTES

- GUARDRAIL DESIGN LOAD TO RESIST A MINIMUM OF 200 LBS LATERAL FORCE.
- ALL GLASS IN INTERIOR AND EXTERIOR DOORS TO BE TEMPERED (INCLUDING SIDE LITES AND TRANSOMS).
- IN THE GARAGE, PROVIDE 1/2" GYP. BOARD AT ALL WALLS COMMON TO LIVING SPACE AND ALL STRUCTURAL MEMBERS SUPPORTING FLOOR/CEILING ASSEMBLY. GARAGE CEILING TO BE 1/2" SAG RESISTANT GYP. BOARD WHEN THERE ARE NO HABITABLE SPACES ABOVE, OR 5/8" TYPE X GYP. BOARD WHEN HABITABLE SPACES ARE ABOVE.
- STAIRS IN LOWER LEVEL: IF THERE IS A DOOR INTO SPACE UNDER STAIR, THEN 1/2" GYP. BOARD REQ'D ON INSIDE OF STORAGE SPACE & UNDERSIDE OF STAIR IF THERE IS NO DOOR INTO SPACE
- UNDER STAIR, IT IS CONSIDERED OPEN AND NO GYP. BOARD IS REQ'D.

### MECHANICAL NOTES

- SMOKE DETECTORS TO BE 110V AND HARD WIRED. PROVIDE BATTERY BACK-UP AND INTERCONNECT (WHEN ONE SOUNDS, ALL SOUND).
- ALL GAS APPLIANCES MUST BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.
- A STAIR HANDRAIL, ON ONE SIDE ONLY, SHALL BE CONTINUOUS FOR THE ENTIRE LENGTH OF THE STAIRWAY, AND ENDS SHALL BE RETURNED TO A WALL OR POST. THE HANDRAIL MAY BE INTERRUPTED AT A NEWEL POST AT A TURN.
- HANDRAILS SHALL BE INSTALLED ON ALL STAIRS WITH 3 OR MORE RISERS, HANDRAIL HEIGHT SHALL BE 34" MIN. / 38" MAX.
- ALL HANDRAIL GRIP PORTIONS SHALL NOT EXCEED 2 5/8" IN CROSS-SECTIONAL DIMENSION.
- KITCHEN BACKSPLASH OUTLETS TO BE LAID FLAT, 37-1/4" FROM TOP OF SUBFLOOR TO BOTTOM OF BOX.
- GUARDRAILS TO BE 36" (MIN.) HIGH. GUARDRAILS AT THE OPEN SIDES OF STAIRS TO BE 36" (MIN.) HIGH, MEASURED VERTICALLY FROM THE NOSING OF THE TREADS. THE HORIZONTAL SPACING OF THE VERTICAL BALUSTERS SHALL BE 4" O.C.
- GROUND FAULT CIRCUIT INTERRUPTER (GFCI) OUTLETS TO BE INSTALLED PER NEC 2017, SECT. 210.8; ADD TAMPER RESISTANT AND GFCI.
- ARC FAULT CIRCUIT OUTLETS TO BE INSTALLED PER NEC 2017, SECT. 210.12
- PROVIDE HOSE BIBS PER DIVISION SPEC. SHEET. EXACT LOCATION TO BE FIELD DETERMINED, UNLESS OTHERWISE NOTED ON THE PLANS.
- MIN. 50 C.F.M. FOR ALL EXHAUST FANS IN BATHROOMS
- ALL HOUSES TO HAVE A PROGRAMMABLE THERMOSTAT.
- TO COMPLY WITH SECTION 405 OF THE 2018 IECC (PERFORMANCE PATH).

### SECTION, DETAILS & ROOF PLAN NOTES

- PRE-ENGINEERED WOOD TRUSSES @ 24" O.C. UNLESS NOTED OTHERWISE.
- SEE TRUSS MANUFACTURER'S SHOP DRAWINGS FOR TRUSS LAYOUT AND DESIGN INCLUDING GIRDER TRUSSES AND BEAM LOCATIONS.
- ALL GIRDER TRUSSES TO BE BOLTED TOGETHER ACCORDING TO MANUFACTURER'S SPECIFICATIONS.
- TRUSSES TO BE BRACED AND INSTALLED ACCORDING TO MANUFACTURER SPECIFICATIONS.
- TRUSS MANUFACTURER'S DIMENSIONS ARE TO OUTSIDE OF SHEATHING.
- ROOF TRUSS MANUFACTURER TO SPECIFY ALL CONNECTIONS AND HANGERS ON SHOP DRAWINGS.
- REFER TO HIB-91 OF TPI (TRUSS PLATE INSTITUTE) FOR SPECIFIC BRACING RECOMMENDATIONS AND REQUIREMENTS.
- TRUSS MANUFACTURER TO PROVIDE ENGINEERED TRUSS DRAWINGS TO THE FIELD ALONG w/ HIB-91 PRIOR TO ERECTION OF TRUSSES.
- PROVIDE A 2x4 LEDGER TO ACCEPT ROOF SHEATHING WHERE A FIRST FLOOR ROOF MEETS THE SIDE OF A SECOND FLOOR.
- PROVIDE 15# FELT PAPER UNDER SHINGLES
- CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL TEMPORARY SHORING AND BRACING DURING CONSTRUCTION FOR ALL ELEMENTS INCLUDING WALLS, JOISTS, TRUSSES, COLUMNS, MASONRY AND OTHERS AS REQUIRED.
- PROVIDE ICE AND WATER GUARD AT ALL EAVES AND VALLEYS.
- ROOF TRUSSES WILL BE FASTENED BY CONNECTORS THAT WILL RESIST A MINIMUM OF 175 LBS OF UPLIFT
- PROVIDE 7/16" ROOF SHEATHING.
- INSTALLATION OF AN ICE BARRIER IS REQUIRED. THE ICE BARRIER SHALL CONSIST OF NOT FEWER THAN TWO LAYERS OF UNDERLAYMENT CEMENTED TOGETHER, OR A SELF-ADHERING POLYMER-MODIFIED BITUMEN SHEET SHALL BE USED IN PLACE OF NORMAL UNDERLAYMENT AND EXTEND FROM THE LOWEST EDGES OF ALL ROOF SURFACES TO A POINT NOT LESS THAN 24 INCHES INSIDE THE EXTERIOR WALL LINE OF THE BUILDING. THE 24 INCH MEASUREMENT SHALL BE ALONG THE SLOPE OF THE ROOF FROM THE POINT WHERE THE PROJECTED OUTSIDE FACE OF THE WALL INTERSECTS THE ROOF DECK. ON ROOFS WITH SLOPE EQUAL TO OR GREATER THAN EIGHT UNITS VERTICAL IN 12 UNITS HORIZONTAL (67-PERCENT SLOPE), THE ICE BARRIER SHALL ALSO BE APPLIED NOT LESS THAN 36 INCHES (914 MM) MEASURED ALONG THE ROOF SLOPE FROM THE EAVE EDGE OF THE BUILDING.
- DO NOT LOCATE ROOF TRUSSES ABOVE PARALLEL PLUMBING WALLS AND/OR HVAC CHASES.

### ELEVATION NOTES

- WINDOW STYLE AND MULLIONS MAY VARY FROM ELEVATION DEPENDING UPON MANUFACTURER, STYLE, PATTERN, TYPE, ETC.
- FRONT DOOR COACH LIGHTS (IF ANY) TO BE SET AT 5'-8" ABOVE FINISHED SURFACE.
- GRADE AWAY FROM FOUNDATION WALLS SHALL FALL A MINIMUM OF 6" WITHIN THE FIRST 10'.
- PROVIDE BRICK FLASHING AND WEEP HOLES WITH WEEP CARDS AT 24" O.C. WITH BRICK VENEER.
- PROVIDE FLASHING AND WEEP HOLES AT 32" O.C. ABOVE BRICK ANGLE IRONS.
- PROVIDE BRICK WALL TIES AT 16" O.C. HORIZONTALLY AND VERTICALLY. PROVIDE BRICK WALL TIES WITHIN 12" OF ANY BRICK OPENINGS AT A MAXIMUM OF 36" O.C. AROUND OPENING.
- WRAP ALL FRIEZE AND FASCIA TRIM BOARDS IN ALUMINUM.
- REFER TO DETAIL ON SHEET IN THE BUILDER BOOK FOR STONE INSTALLATION DETAILS.
- PAD OUT ALL GABLE ENDS (WITHOUT GABLE EXTENSIONS) W/ (2) 1x3s PLACED SIDE BY SIDE WITH THE 1x8 OVER THE TOP TO COVER THE ENDS OF THE SIDING.
- USE EXTERIOR PROTECTIVE COVERINGS ON ALL DIRECT VENT FIREPLACES (IF ANY).
- EXTERIOR STEPS TO HAVE A MAXIMUM 8" RISER. WHEN VERTICAL RISE EXCEEDS 30" OR FOUR OR MORE CONTINUOUS RISERS, A HANDRAIL IS REQUIRED.

2019 RESIDENTIAL CODE OF OHIO METHOD  
USED FOR CHAPTER 11 ENERGY EFFICIENCY  
OHBA PATH #2 (SECTION 1112)

WALLS R VALUE R13

CEILINGS R VALUE R49

WINDOWS U VALUE 32U

BASEMENT FOUNDATION WALLS R11 4 FT  
DOWN ALL WALLS

FLOOR OVER UNCONDITIONED SPACE R30

RIM JOIST R13

INCLUDES ALL DESIGNATED MANDATORY  
CODE SECTIONS CHAPTER 11

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDEMEER**  
**ELEVATE**

Job Number: DOYL-0201-00 Drawing Date: 09/24/25 Coord Name: LUKE RAMLER Coord Phone: (859)-578-4212

House Name: the NORTHWOOD Drawing Scale: 1/8" = 1'-0" Series: SERIES II


Plan No.:

**Drees**  
HOMES<sup>SM</sup>

Sheet Information

**ON.1**  
GENERAL NOTES SHEET  
ELEVATION "E"


Copyright © 2016. (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD. SUITE 150. BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670



REISSUED: 10/10/25

General Notes			
<ul style="list-style-type: none"> <li>- REFER TO SHEET ON.1 FOR GENERAL NOTES.</li> <li>- ALL FOUNDATION WALLS 8'-0" TALL AND 8" THICK, UNLESS OTHERWISE NOTED.</li> <li>- OVERALL FOUNDATION WALL HEIGHT MAY VARY UP TO 1".</li> <li>- SEE SHEET ON.1 FOR VERTICAL FOUNDATION WALL CONTROL JOINT LOCATIONS.</li> </ul>			
<b>Key Notes</b>			
<ul style="list-style-type: none"> <li>1 SLAB CONTROL JOINT</li> <li>2 SLAB CONTROL JOINT TO BE LOCATED DIRECTLY UNDER STEEL BEAM</li> <li>3 36x36x12 PLAIN CONCRETE PAD TYP. U.N.O.</li> <li>4 8" Wx8" Hx4" D BEAM POCKET</li> <li>5</li> <li>6 3-1/2" DIA. STEEL P.C. (16.0k MIN. CAP. ASD)</li> <li>7 CONTINUOUS FOOTING AND FOUNDATION-DROP TO BE FIELD DETERMINED.</li> <li>8 5'-0" DIAMETER AREA SLOPED TO DRAIN WITH 2" LOWER THAN TOP OF SLAB</li> <li>9 GARAGE SLAB TO BE HELD A MINIMUM OF 4" BELOW TOP OF FOUNDATION AND IS TO SLOPE 4" TOWARDS GARAGE DOOR.</li> <li>10 OUTLINE OF BASEMENT STAIR AND BEARING WALL</li> <li>11 3-1/2" DIA. STEEL P.C. (14.3k MIN. CAP. ASD)</li> <li>12 LINE OF STUD WALL/PORCH SLAB ABOVE. SEE TYPICAL PORCH SECTION E/7.01 FOR DETAILS</li> <li>13 6x6 P.T. POST W/ SIMPSON BCS2-3/6 CAP &amp; ABW66Z BASE ON 18" DIA. SONOTUBE FOOTING TO FROST</li> <li>14 CONCRETE OVERHANG AT FRONT PORCH (1-1/2" TYP.)</li> <li>15 3x5-1/2" NOTCH FOR GARAGE DOOR TRACK. DROP TO BE FIELD DETERMINED TO CATCH GARAGE SLAB - SEE DETAIL C/7.01</li> <li>16 3-1/2" DIA. STEEL P.C. (11.1k MIN. CAP. ASD)</li> <li>17 3-1/2" DIA. STEEL P.C. (18.0k MIN. CAP. ASD)</li> <li>18 30'x30'x12" PLAIN CONCRETE PAD TYP. U.N.O.</li> <li>19 8" Wx10" Hx4" D BEAM POCKET</li> <li>20 BOTTOM OF WINDOW SILL @ 40" A.F.F. MAX FOR EGRESS W/ 12" MIN. CONC. HEADER</li> <li>21 STD. BASEMENT WINDOW PER DIVISION Specs. TOP OF WINDOW TO BE FLUSH WITH TOP OF FOUNDATION WALL WITH (1) 3-1/4" X 11-7/8" LVL (FLUSH) OR CONT. RIM JOIST - FIELD DETERMINE</li> <li>22 P.T. LEDGER FASTENED TO FOUNDATION WALL - RE: DETAIL SHEET D7.7 FOR FRAMING</li> <li>23 24x24x12" PLAIN CONCRETE PAD TYP. U.N.O.</li> <li>24 3-1/2" DIA. STEEL P.C. (4.0k MIN. CAP. ASD)</li> <li>25 3-1/2" DIA. STEEL P.C. (5.2k MIN. CAP. ASD)</li> <li>26 3-1/2" DIA. STEEL P.C. (13.4k MIN. CAP. ASD)</li> </ul>			
<b>RESIDENCE FOR:</b> <b>KLEINMAN</b> <b>3759 BENDEMER</b> <b>ELEVATE</b> <b>the NORTHWOOD</b>			
Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212
House Name:	Drawing Scale:	1/8" = 1'-0"	Series:
			SERIES II
			Plan No.:
		Sheet Information	1.01
Copyright © 2016. (2016) The Drees Company. All Rights Reserved. 6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141 PHONE: (440) 717-9670			

ALL SLEEPING ROOM WINDOWS WILL  
COMPLY WITH RCO310



## General Notes

- REFER TO SHEET ON.1 FOR GENERAL NOTES.

## Key Notes

- 1
- 2
- 3
- 4
- 5
- 6 2x4 STUDS HELD 1" FROM FOUNDATION WALL WITH 3-1/2" BATT INSULATION
- 7 RIPPED 1x\_ FOR WOOD SILL
- 8 SLOPED WALL WITH STAIR STRINGER
- 9 BOX OUT AROUND COLUMNS AND BEAMS IN FINISHED AREAS
- 10 80 SQ. FT. MAX. AREA OF CEILING, COMPLYING WITH RCO 302.13 EXCEPTION 3.1 & EXCEPTION 3.2, NOT REQUIRING DRYWALL. PERIMETER EDGE MUST BE FIREBLOCKED TO KEEP SEPARATE FROM THE REST OF THE FLOOR ASSEMBLY.
- 11 UNFINISHED BASEMENT CEILING TO BE COVERED IN 1/2" GYPSUM BOARD (WITH THE EXCEPTION OF THE AREA OF KEYNOTE 10). JOINTS DO NOT NEED TO BE TAPE OR MUDDED.
- 12
- 13
- 14
- 15

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDEMEER**  
**FIFVATE**

Job Number: DOYL-0201-00	Drawing Date: 09/24/25	Coord Name: LUKE RAMLER	Coord Phone: (859)-578-4212
House Name: the NORTHWOOD		Drawing Scale: 1/8" = 1'-0"	Series: SERIES II
			Plan No.:

the NORTHWOOD


 **Drees**  
HOMES<sup>®</sup>

Copyright © 2014. (2014) The Drees Company. All Rights Reserved.

Sheet Information

1.02

**LOWER LEVEL FRAMING PLAN**  
**ELEVATION "E"**



#### General Notes

- REFER TO SHEET 0N.1 FOR GENERAL NOTES.

#### Key Notes

- [1] -
- [2] TO SWITCH ABOVE.
- [3] OUTLET IN JOIST SPACE
- [4] -
- [5] -
- [6] -
- [7] -
- [8] -
- [9] -
- [10] -

#### Mechanical Legend

◀ DATA JACK	FLUORESCENT LIGHT
⊖ W.O. WALL OUTLET	UNDER CABINET LIGHTING
⊖ GFCI OUTLET	CLG. MOUNTED LIGHT FIX.
⊖ 220 OUTLET	WALL MOUNTED LIGHT FIX.
⊖ GFCI OUTLET	SURFACE MOUNT DISC LIGHT OR RECESSED CEILING LIGHT, PER SPEC.
⊖ FLOOR OUTLET	DOUBLE SPOTLIGHT FIX.
⊖ COUNTER POP-UP OUTLET	PIN LIGHT
⊖ CABLE TELEVISION JACK	WALL SCONCE @ 5'-6" A.F.F.
⊖ SING. POLE SWITCH	STAIR LIGHT
⊖ 3-WAY SWITCH	CLG. MTD. EXHAUST FAN
⊖ 4-WAY SWITCH	WALL MTD. EXHAUST FAN
⊖ SMOKE DETECTOR	SHOWER HEAD
⊖ SMOKE DETECTOR/CO DETECTOR COMBINATION	HOSE BIB
⊖ BLOCK, MOUNT, & SWITCH FOR FUTURE FAN/LIGHT COMBINATION (CENTER, UNLESS OTHERWISE NOTED)	GAS HOOK UP
⊖ EXHAUST FAN AND LIGHT COMBINATION	GAS
⊖ FLOOR DRAIN	FLOOR DRAIN

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDEMEER**  
**ELEVATE**

Job Number: DOYL-0201-00 Drawing Date: 09/24/25 Coord Name: LUKE RAMLER Coord Phone: (859)-578-4212

House Name: Drawing Scale: 1/8" = 1'-0" Series: SERIES II


the NORTHWOOD

**1.03**


LOWER LEVEL MECHANICAL PLAN  
ELEVATION "E"



Sheet Information



<b>General Notes</b> <ul style="list-style-type: none"> <li>REFER TO SHEET ON.1 FOR GENERAL NOTES.</li> <li>ALL FIRST FLOOR CEILINGS TO BE 9'1" ABOVE SUBFLOOR UNLESS OTHERWISE NOTED.</li> <li>FRAME TOP OF ALL WINDOWS @ 10'-1/4" BELOW TOP PLATE UNLESS OTHERWISE NOTED.</li> <li>ALL DROPPED INTERIOR HEADERS TO BE DROPPED 1'-0" FROM CEILING UNLESS OTHERWISE NOTED.</li> </ul>			
<b>Key Notes</b>			
1	34-1/2" HIGH WALL		
2	FRAME WALL @ 10'-3 1/8" WITH 2x4's AT 12" O.C. ABOVE FOUNDATION WALL		
3	SECOND FLOOR LINE ABOVE		
4	FALSE HEADER		
5	HVAC CHASE		
6	LEDGE OF FOUNDATION WALL		
7	SLOPE WALL WITH STAIR STRINGER		
8	CARPENTER TO DROP ELECTRICAL WIRE THROUGH PORCH CEILING FOR LIGHTS		
9	10'x10" BOX COLUMN RE: DETAIL A/7.01 FOR FRAMING		
10	--		
11	--		
12	--		
13	--		
14	--		
15	--		
16	--		
17	--		
18	--		
19	--		
20	--		
<b>RESIDENCE FOR:</b> <b>KLEINMAN</b> <b>3759 BENDEMEER</b> <b>ELEVATE</b>			
Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212
House Name:	Drawing Scale:	Series:	
	1/8" = 1'-0"	SERIES II	
<b>the NORTHWOOD</b>			
<b>drees</b> <b>HOMES</b> SM			
Copyright © 2016, (2016) The Drees Company. All Rights Reserved. 6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141 PHONE: (440) 717-9670			
Sheet Information	2.01F		
1ST FLOOR FRAMING PLAN ELEVATION "E"			



### General Notes

- REFER TO SHEET 0N.1 FOR GENERAL NOTES.

### Key Notes

- 1 BEARING WALL
- 2 4x4 P.T. POST W/ SIMPSON BC2-2/4 POST CAP AND ABW44Z POST BASE (TYP.)
- 3 TOP OF FRONT PORCH HEADER 9'-1" A.F.F.
- 4
- 5 SIMPSON HU11 HANGER
- 6
- 7
- 8
- 9 SIMPSON HUC412 HANGER
- 10

### CONNECTION SPECIFICATIONS (TYP. U.N.O.)

NOTE: 10d NAIL = 3" x 0.131" GUN NAIL

JOIST TO SOLE PLATE	(3) 10d TOENAILS
SOLE PLATE TO JOIST/BLK'G.	10d NAILS @ 6" o.c.
STUD TO SOLE PLATE	(3) 10d TOENAILS
TOP OR SOLE PLATE TO STUD	(3) 10d NAILS
RIM TO TOP PLATE	10d TOENAILS @ 6" o.c.
BLK'G. BTWN. JOISTS TO TOP PL.	(3) 10d TOENAILS
RAFTER/TRUSS TO TOP PLATE	(3) 10d TOENAILS + (1) SIMPSON H2.5A
GAB. END TRUSS TO DBL. TOP PL.	10d TOENAILS @ 8" o.c.
R.T. w/ HEEL HT. 9 1/4" TO 12"	2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" o.c.
R.T. w/ HEEL HT. 12" TO 16"	2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" o.c.
R.T. w/ HEEL HT. UP TO 24"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" o.c.
R.T. w/ HEEL HT. 24" TO 48"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" o.c. PROVIDE 2x BLK @ EA. BAY AT TOP OF HEEL
DOUBLE STUD	10d NAILS @ 24" o.c.
DOUBLE TOP PLATE	10d NAILS @ 24" o.c.
DOUBLE TOP PLATE LAP SPLICING	(10) 10d NAILS IN LAPPED AREA
TOP PLATE LAP @ CORNERS & INTERSECTING WALLS	(2) 10d NAILS
WALL TO FOUNDATION	WALL SHTG. LAP w/ SILL PL. & FASTENED PER SHEAR WALL FASTENING SPEC.

### RESIDENCE FOR:

**KLEINMAN**  
**3759 BENDEMEER**  
**ELEVATE**

Job Number: DOYL-0201-00 Drawing Date: 09/24/25 Coord Name: LUKE RAMLER Coord Phone: (859)-578-4212

House Name: Drawing Scale: 1/8" = 1'-0" Series: SERIES II

Plan No.: the NORTHWOOD

**drees**  
HOMES<sup>SM</sup>


Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Sheet Information

**2.01S**

1ST FLOOR STRUCTURAL PLAN  
ELEVATION "E"

REISSUED: 10/10/25



ALL SLEEPING ROOM WINDOWS WILL COMPLY WITH RCO310

#### General Notes

- REFER TO SHEET ON J FOR GENERAL NOTES.
- ALL SECOND FLOOR CEILINGS TO BE 8'1" ABOVE SUBFLOOR UNLESS OTHERWISE NOTED.
- FRAME TOP OF ALL WINDOWS @ 10'-1/4" BELOW TOP PLATE UNLESS OTHERWISE NOTED.
- ALL DROPPED INTERIOR HEADERS TO BE DROPPED 1'-0" FROM CEILING UNLESS OTHERWISE NOTED.

#### Key Notes

- 1 36" HIGH WALL.
- 2 OUTLINE OF GARAGE OR FIRST FLOOR WALL BELOW.
- 3
- 4 HVAC CHASE
- 5 TAP AND DRAIN
- 6
- 7 22-1/2" x 32' ATTIC ACCESS.
- 8 WASHER TO LEFT OF DRYER
- 9 BOTTOM OF WINDOW AT 30-3/4" A.F.F.
- 10 --
- 11 --
- 12 --
- 13 --
- 14 --
- 15 --
- 16 --
- 17 --
- 18 --
- 19 --
- 20 --

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212

House Name:	Drawing Scale: 1/8" = 1'-0"	Series:
the NORTHWOOD		SERIES II

Plan No.:	
-----------	--


**drees**  
HOMES<sup>SM</sup>

Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Sheet Information


**2.02F**

2ND FLOOR FRAMING PLAN  
ELEVATION "E"



<b>General Notes</b> - REFER TO SHEET ON.1 FOR GENERAL NOTES.																																					
<b>Key Notes</b>																																					
<input type="checkbox"/> 1 SHEATH EXT. WALL W/ PLYWOOD/OSB CONT. BEHIND LOW ROOF DOWN TO SECOND FLOOR <input type="checkbox"/> 2																																					
<b>CONNECTION SPECIFICATIONS (TYP. U.N.O.)</b>																																					
<p>NOTE: 10d NAIL = 3" x 0.131" GUN NAIL</p> <table border="1"> <tr> <td>JOIST TO SOLE PLATE</td><td>(3)10d TOENAILS</td></tr> <tr> <td>SOLE PLATE TO JOIST/BLK'G.</td><td>10d NAILS @ 6" o.c.</td></tr> <tr> <td>STUD TO SOLE PLATE</td><td>(3)10d TOENAILS</td></tr> <tr> <td>TOP OR SOLE PLATE TO STUD</td><td>(3)10d NAILS</td></tr> <tr> <td>RIM TO TOP PLATE</td><td>10d TOENAILS @ 6" o.c.</td></tr> <tr> <td>BLK'G. BTWN. JOISTS TO TOP PL.</td><td>(3)10d TOENAILS</td></tr> <tr> <td>RAFTER/TRUSS TO TOP PLATE</td><td>(3)10d TOENAILS + (1) SIMPSON H2.5A</td></tr> <tr> <td>GAB. END TRUSS TO DBL. TOP PL.</td><td>10d TOENAILS @ 8" o.c.</td></tr> <tr> <td>R.T. w/ HEEL HT. 9 1/4" TO 12"</td><td>2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.</td></tr> <tr> <td>R.T. w/ HEEL HT. 12" TO 16"</td><td>2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.</td></tr> <tr> <td>R.T. w/ HEEL HT. UP TO 24"</td><td>LAP WALL SHTG. w/ DBL. TOP PL. &amp; INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C.</td></tr> <tr> <td>R.T. w/ HEEL HT. 24" TO 48"</td><td>LAP WALL SHTG. w/ DBL. TOP PL. &amp; INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C. PROVIDE 2x BLK @ EA. BAY AT TOP OF HEEL</td></tr> <tr> <td>DOUBLE STUD</td><td>10d NAILS @ 24" o.c.</td></tr> <tr> <td>DOUBLE TOP PLATE</td><td>10d NAILS @ 24" o.c.</td></tr> <tr> <td>DOUBLE TOP PLATE LAP SPLIC</td><td>(10)10d NAILS IN LAPPED AREA</td></tr> <tr> <td>TOP PLATE LAP @ CORNERS &amp; INTERSECTING WALLS</td><td>(2)10d NAILS</td></tr> <tr> <td>WALL TO FOUNDATION</td><td>WALL SHTG. LAP w/ SILL PL. &amp; FASTENED PER SHEAR WALL FASTENING SPEC.</td></tr> </table>				JOIST TO SOLE PLATE	(3)10d TOENAILS	SOLE PLATE TO JOIST/BLK'G.	10d NAILS @ 6" o.c.	STUD TO SOLE PLATE	(3)10d TOENAILS	TOP OR SOLE PLATE TO STUD	(3)10d NAILS	RIM TO TOP PLATE	10d TOENAILS @ 6" o.c.	BLK'G. BTWN. JOISTS TO TOP PL.	(3)10d TOENAILS	RAFTER/TRUSS TO TOP PLATE	(3)10d TOENAILS + (1) SIMPSON H2.5A	GAB. END TRUSS TO DBL. TOP PL.	10d TOENAILS @ 8" o.c.	R.T. w/ HEEL HT. 9 1/4" TO 12"	2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.	R.T. w/ HEEL HT. 12" TO 16"	2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.	R.T. w/ HEEL HT. UP TO 24"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C.	R.T. w/ HEEL HT. 24" TO 48"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C. PROVIDE 2x BLK @ EA. BAY AT TOP OF HEEL	DOUBLE STUD	10d NAILS @ 24" o.c.	DOUBLE TOP PLATE	10d NAILS @ 24" o.c.	DOUBLE TOP PLATE LAP SPLIC	(10)10d NAILS IN LAPPED AREA	TOP PLATE LAP @ CORNERS & INTERSECTING WALLS	(2)10d NAILS	WALL TO FOUNDATION	WALL SHTG. LAP w/ SILL PL. & FASTENED PER SHEAR WALL FASTENING SPEC.
JOIST TO SOLE PLATE	(3)10d TOENAILS																																				
SOLE PLATE TO JOIST/BLK'G.	10d NAILS @ 6" o.c.																																				
STUD TO SOLE PLATE	(3)10d TOENAILS																																				
TOP OR SOLE PLATE TO STUD	(3)10d NAILS																																				
RIM TO TOP PLATE	10d TOENAILS @ 6" o.c.																																				
BLK'G. BTWN. JOISTS TO TOP PL.	(3)10d TOENAILS																																				
RAFTER/TRUSS TO TOP PLATE	(3)10d TOENAILS + (1) SIMPSON H2.5A																																				
GAB. END TRUSS TO DBL. TOP PL.	10d TOENAILS @ 8" o.c.																																				
R.T. w/ HEEL HT. 9 1/4" TO 12"	2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.																																				
R.T. w/ HEEL HT. 12" TO 16"	2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.																																				
R.T. w/ HEEL HT. UP TO 24"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C.																																				
R.T. w/ HEEL HT. 24" TO 48"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" O.C. PROVIDE 2x BLK @ EA. BAY AT TOP OF HEEL																																				
DOUBLE STUD	10d NAILS @ 24" o.c.																																				
DOUBLE TOP PLATE	10d NAILS @ 24" o.c.																																				
DOUBLE TOP PLATE LAP SPLIC	(10)10d NAILS IN LAPPED AREA																																				
TOP PLATE LAP @ CORNERS & INTERSECTING WALLS	(2)10d NAILS																																				
WALL TO FOUNDATION	WALL SHTG. LAP w/ SILL PL. & FASTENED PER SHEAR WALL FASTENING SPEC.																																				
<b>RESIDENCE FOR:</b> <b>KLEINMAN</b> <b>3759 BENDMEER</b> <b>ELEVATE</b>																																					
Job Number:	Drawing Date:	Coord Name:	Coord Phone:																																		
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212																																		
House Name:	Drawing Scale:	1/8" = 1'-0"	Series:																																		
the NORTHWOOD			SERIES II																																		
			Plan No.:																																		
		2.02S	Sheet Information																																		
2ND FLOOR STRUCTURAL PLAN ELEVATION "E"																																					

REISSUED: 10/10/25



HEEL CUT STANDARD			
ROOF PITCH	OVERHANG		
	1'-0"	2'-0"	
4:12	3-3/4"	7-3/4"	
5:12	4-3/4"	9-3/4"	
6:12	5-3/4"	11-3/4"	
7:12	6-3/4"	13-3/4"	
8:12	7-3/4"	N/A	
9:12	8-3/4"	N/A	
10:12	9-3/4"	N/A	
12:12	11-3/4"	N/A	
14:12	13-3/4"	N/A	

# CONNECTION SPECIFICATIONS (TYP. U.N.O.)

NOTE: 10d NAIL = 3" x 0.131" GUN NAIL	
JOIST TO SOLE PLATE	(3)10d TOENAILS
SOLE PLATE TO JOIST/BLK'G.	10d NAILS @ 6" o.c.
STUD TO SOLE PLATE	(3)10d TOENAILS
TOP OR SOLE PLATE TO STUD	(3)10d NAILS
RIM TO TOP PLATE	10d TOENAILS @ 6" o.c.
BLK'G. BTWN. JOISTS TO TOP PL.	(3)10d TOENAILS
RAFTER/TRUSS TO TOP PLATE	(3)10d TOENAILS + (1) SIMPSON H.2.5A
GAB. END TRUSS TO DBL. TOP PL.	10d TOENAILS @ 8" o.c.
R.T. w/ HEEL HT. 9 $\frac{3}{4}$ " TO 12"	2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" o.c.
R.T. w/ HEEL HT. 12" TO 16"	2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" o.c.
R.T. w/ HEEL HT. UP TO 24"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" o.c.
R.T. w/ HEEL HT. 24" TO 48"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN w/ 8d NAILS @ 6" o.c. PROVIDE 2x BLK @ EA. BAY AT TOP OF HEEL
DOUBLE STUD	10d NAILS @ 24" o.c.
DOUBLE TOP PLATE	10d NAILS @ 24" o.c.
DOUBLE TOP PLATE LAP SPLICING	(10)10d NAILS IN LAPPED AREA
TOP PLATE LAP @ CORNERS & INTERSECTING WALLS	(2)10d NAILS
WALL TO FOUNDATION	WALL SHTG. LAP w/ SILL PL. & FASTENED PER SHEAR WALL FASTENING SPEC.

TRUSS MANUFACTURER TO VERIFY THE FOLLOWING:  
(REFER TO SHEETS 2.01F AND/OR 2.02F)

1) DO NOT LOCATE ROOF TRUSSES ABOVE PARALLEL PLUMBING WALLS  
OR KITCHEN HOOD WALLS

2) DO NOT LOCATE ROOF TRUSSES ABOVE HVAC CHASES (OR LEAVE  
A MIN. 22-1/2" WIDE CLEAR SPACE OVER CHASE)

1

REFER TO SHEET ON.1 FOR GENERAL NOTES.

## Key Notes

- 1
- 2 VALLEY TRUSS OVERFRAMING AT 24" O.C.
- 3
- 4 NO ROOF DECKING IN THIS AREA TO ALLOW FOR PROPER ATTIC VENTILATION
- 5
- 6
- 7
- 8
- 9
- 10

## ROOF VENTILATION

ITY/SERIES: **CLEVELAND**  
MAIN HOUSE

TOTAL ATTIC AREA: 2,129  
REQUIRED NET FREE VENTILATION (ATTIC AREA/300): 7.10  
ACTUAL NET FREE VENTILATION (UPPER + LOWER): 7.20

## DOwnspout Calculation

MAIN HOUSE	
TOTAL DRAINABLE ROOF AREA:	2767.7
MINIMUM # OF DOWNSPOUTS:	5

## RESIDENCE FOR:

KLEINMAN

**3759 BENDUMEER  
ELEVATE**

**Job Number:** **Drawing Date:** **Coord Name:** **Coord Phone:**

DOYL-0201-00 09/24/25 LUKE RAMLER (859)-578-4212

House Name: Drawing Scale: 1/8" = 1'-0" Series:

# the NORTHWOOD


**drees**  
**HOMES** SM

Sheet Information

2.04

ROOF PLAN  
ELEVATION "F"

**ROOF PLAN**  
**ELEVATION "F"**



REISSUED: 10/10/25

## General Notes

REFER TO SHEET ON.1 FOR GENERAL NOTES.  
JOISTS ARE NOT TO BE PLACE DIRECTLY OVER INTERIOR PARALLEL WALL. (TO PREVENT UNEVEN FLOOR DEFLECTION FROM OCCURRING)  
PROVIDE I-JOIST PROTECTION AS REQUIRED BY RCO 2013 SECTION 502.14

## Key Notes

- 1
- 2 BEAM BELOW - SEE SHEET 1.01 FOR SIZE
- 3 PLUMBING STACK
- 4 BEARING WALL ABOVE
- 5 BASEMENT WINDOW HEADER TO BE HELD FLUSH IN SUBFLOOR: PROVIDE 1-3/4" x 11-7/8" LVL AND/OR REFER TO ENGINEERED PLAN FOR SPECIFICATIONS. OPT. LARGER WINDOWS TO USE CONCRETE HEADERS
- 6 DOUBLE EVERY OTHER JOIST UNDER KITCHEN ISLAND (MIN. 2 INSTANCES)
- 7 FLUSH BEAM - SEE 1.01 STRUCTURAL SHEET AND MANUFACTURER SPECIFICATIONS FOR INFORMATION
- 8 2x10 FLAT FRAME
- 9 CHASE FOR HVAC
- 10 80 SQ. FT. MAX. AREA OF CEILING, COMPLYING WITH RCO 302.13 EXCEPTION 3.1 & EXCEPTION 3.2, NOT REQUIRING DRYWALL. PERIMETER EDGE MUST BE FIREBLOCKED TO KEEP SEPARATE FROM THE REST OF THE FLOOR ASSEMBLY.
- 11 --
- 12 --
- 13 --
- 14 --
- 15 --
- 16 --
- 17 --
- 18 --
- 19 --
- 20 --

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDEMEER**  
**FIFVATE**


Job Number: <b>DOYL-0201-00</b>	Drawing Date: <b>09/24/25</b>	Coord Name: <b>LUKE RAMLER</b>	Coord Phone: <b>(859)-578-4212</b>
House Name: <b>the NORTHWOOD</b>	Drawing Scale: <b>1/8" = 1'-0"</b>		Series: <b>SERIES II</b>
			Plan No.:

# the NORTHWOOD

The logo for Drees Homes, featuring the word "drees" in a large, bold, dark green sans-serif font, with "HOMES" in a smaller, dark green sans-serif font below it. To the left of "drees" is a small, stylized green square icon.

Sheet Information

3.01



REISSUED: 10/10/25

#### General Notes

- REFER TO SHEET 01 FOR GENERAL NOTES.
- FLOOR SYSTEM AS NOTED, THIS SHEET.
- JOISTS ARE NOT TO BE PLACE DIRECTLY OVER INTERIOR PARALLEL WALL. (TO PREVENT UNEVEN FLOOR DEFLECTION FROM OCCURRING)

#### Key Notes

- [1] BEARING WALL BELOW
- [2] BEAM BELOW - SEE 2.01 STRUCTURAL SHEET AND MANUFACTURER SPECIFICATIONS FOR INFORMATION
- [3] PLUMBING STACK
- [4] FLUSH BEAM - SEE 2.01 STRUCTURAL SHEET AND MANUFACTURER SPECIFICATIONS FOR INFORMATION
- [5]
- [6] PROVIDE DOUBLE JOISTS AND BLOCKING FOR HVAC CHASE
- [7]
- [8]
- [9] --
- [10] --
- [11] --
- [12] --
- [13] --
- [14] --
- [15] --
- [16] --
- [17] --
- [18] --
- [19] --
- [20] --

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212

House Name:	Drawing Scale: 1/8" = 1'-0"	Series:
the NORTHWOOD		SERIES II


Plan No.:
-----------

**Drees**  
HOMES<sup>SM</sup>



Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Sheet Information

**3.02**  
2nd FLOOR SUB-FLOOR PLAN  
ELEVATION "E"







#### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.

#### Key Notes

- 1 HVAC CHASE
- 2 OUTLET IN CEILING
- 3 TO SWITCH OR LIGHT BELOW
- 4 TO SWITCH OR LIGHT ABOVE
- 5 OUTLINE OF SECOND FLOOR ABOVE
- 6 OUTLET HELD HIGH FOR FUTURE MICROWAVE - VENT TO EXTERIOR
- 7 OUTLET IN SINK CABINET FOR DISHWASHER DISCONNECT
- 8 DISPOSAL SWITCH IN SINK CABINET
- 9
- 10 REFER TO JOBDODC ON DREESBUILD FOR FINAL KITCHEN CABINET LAYOUT
- 11
- 12
- 13 22-1/2" x 32" ATTIC ACCESS.
- 14
- 15

#### Mechanical Legend

◀ DATA JACK	FLUORESCENT LIGHT
⊖ OUTLET	UNDER CABINET LIGHTING
⊖ GFI OUTLET	CLG. MOUNTED LIGHT FIXT.
⊖ 220 OUTLET	WALL MOUNTED LIGHT FIXT.
⊖ GFI OUTLET	SURFACE MOUNT DISC LIGHT OR RECESSED CEILING LIGHT, PER SPECS.
⊖ FLOOR OUTLET	DOUBLE SPOTLIGHT FIXT.
⊖ COUNTER POP-UP OUTLET	DIRECTIONAL CAN LIGHT
⊖ CABLE TELEVISION JACK	PIN LIGHT
⊖ SINGLE POLE SWITCH	WALL SCONCE @ 5'-6" A.F.F.
⊖ 3-WAY SWITCH	STAIR LIGHT
⊖ 4-WAY SWITCH	CLG. MTD. EXHAUST FAN
⊖ SMOKE DETECTOR	WALL MTD. EXHAUST FAN
⊖ SMOKE DETECTOR/CO DETECTOR COMBINATION	SHOWER HEAD
⊖ BLOCK, MOUNT, & SWING FOR FUTURE FAN/LIGHT COMBINATION (CENTER, UNLESS OTHERWISE NOTED)	HOSE BIB
⊖ EXHAUST FAN AND LIGHT COMBINATION	GAS HOOK UP
⊖	FLOOR DRAIN

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number: DOYL-0201-00 Drawing Date: 09/24/25 Coord Name: LUKE RAMLER Coord Phone: (859)-578-4212

House Name: Drawing Scale: 1/8" = 1'-0" Series: SERIES II

the NORTHWOOD Plan No.:


**Drees**  
HOMES<sup>SM</sup>

Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Sheet Information

**4.01**

1ST FLOOR MECHANICAL PLAN  
ELEVATION "E"



### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.

### Key Notes

- [1] TO LIGHT OR SWITCH BELOW
- [2] 22-1/2" x 32" ATTIC ACCESS.
- [3] 36" HIGH TILED HALF WALL
- [4] 16" DEEP SHELF @ 5'7" A.F.F.
- [5] TAP AND DRAIN
- [6] HVAC CHASE
- [7] WASHER TO LEFT OF DRYER
- [8] --
- [9] --
- [10] --
- [11] --
- [12] --
- [13] --

### Mechanical Legend

◀ DATA JACK	FLUORESCENT LIGHT
∅ WALL OUTLET	UNDER CABINET LIGHTING
∅ WEATHERPROOF OUTLET	CLG. MOUNTED LIGHT FIXT.
∅ 220 OUTLET	WALL MOUNTED LIGHT FIXT.
∅ GROUND FAULT CIRCUIT INTERRUPT OUTLET	SURFACE MOUNT DISC LIGHT OR RECESSED CEILING LIGHT, PER SPEC.
∅ FLOOR OUTLET	DOUBLE SPOTLIGHT FIXT.
∅ COUNTER POP-UP OUTLET	DIRECTIONAL CAN LIGHT
∅ CABLE TELEVISION JACK	PIN LIGHT
↔ SINGLE POLE SWITCH	WALL SCONCE @ 5'-6" A.F.F.
↔ 3-WAY SWITCH	STAIR LIGHT
↔ 4-WAY SWITCH	CLG. MTD. EXHAUST FAN
∅ SMOKE DETECTOR	WALL MTD. EXHAUST FAN
∅ SMOKE DETECTOR/CO DETECTOR COMBINATION	SHOWER HEAD
∅ BLOCK, MOUNT, & SWITCH FOR FUTURE FAN/LIGHT COMBINATION (CENTER, UNLESS OTHERWISE NOTED)	HOSE BIB
∅ EXHAUST FAN AND LIGHT COMBINATION	GAS HOOK UP
∅	FLOOR DRAIN

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number:	Drawing Date:	Coord Name:	Coord Phone:
-------------	---------------	-------------	--------------

DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212
--------------	----------	-------------	----------------

House Name:	Drawing Scale: 1/8" = 1'-0"	Series:
-------------	-----------------------------	---------

SERIES II



Plan No.:	
-----------	--

<b>Drees</b> HOMES	<b>4.02</b>
-----------------------	-------------

Copyright © 2016. (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9670

Sheet Information

2ND FLOOR MECHANICAL PLAN  
ELEVATION 'E'



## BUILDING SECTION THROUGH MAIN HOUSE

SCALE: 1/8" = 1'-0"

## General Notes

- REFER TO SHEET ON.1 FOR GENERAL NOTES.

## Key Notes

- 1 -
- 2 -
- 3 -
- 4 -
- 5 -
- 6 -
- 7 -
- 8 -
- 9 -
- 10 -
- 11 -
- 12 -
- 13 -
- 14 -
- 15 -
- 16 -
- 17 -
- 18 -
- 19 -
- 20 -

**RESIDENCE FOR:  
KLEINMAN  
3759 BENDEMEER  
ELEVATE**


Job Number: DOYL-0201-00	Drawing Date: 09/24/25	Coord Name: LUKE RAMLER	Coord Phone: (859)-578-4212
House Name: the NORTHWOOD	Drawing Scale: 1/8" = 1'-0"		Series: SERIES II
			Plan No.:

## the NORTHWOOD



Sheet Information

# 5.01



## General Notes

- REFER TO SHEET ON.1 FOR GENERAL NOTES.

## Key Notes

- 1 -
- 2 -
- 3 -
- 4 -
- 5 -
- 6 -
- 7 -
- 8 -
- 9 -
- 10 -
- 11 -
- 12 -
- 13 -
- 14 -
- 15 -
- 16 -
- 17 -
- 18 -
- 19 -
- 20 -

**RESIDENCE FOR:**

KLEINMAN

**3759 BENDEMEER  
ELEVATE**

Job Number: <b>DOYL-0201-00</b>	Drawing Date: <b>09/24/25</b>	Coord Name: <b>LUKE RAMLER</b>	Coord Phone: <b>(859)-578-4212</b>
House Name: <b>the NORTHWOOD</b>	Drawing Scale: <b>1/8" = 1'-0"</b>		Series: <b>SERIES II</b>




Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
PHONE: (440) 717-9470

### Sheet Information

# 5.02

SECTIONS & DETAILS  
ELEVATION "E"


35'-10 5/8"



## ELEVATION

## RAFTER TAIL OVERHANG DETAIL

SCALE: 1/2" = 1'-0"



REISSUED: 10/10/25

TYPICAL TRIM:	
6" FASCIA - 8" w/ HARDIE SOFITT (ALL SIDES)	
8" FRIEZE (FRONT ONLY UNLESS OTHERWISE NOTED)	

## General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. REFER TO SELECTIONS/SPECIFICATIONS FOR ROOFING MATERIAL.
3. FRONT DOOR AND GARAGE DOOR PER SELECTIONS

## Key Notes

- 1 --
- 2 --
- 3 --
- 4 INTERIOR OF PORCH TO BE BRICK
- 5 --
- 6 --
- 7 --
- 8 --
- 9 --
- 10 --
- 11 --
- 12 --
- 13 --
- 14 --

## BRICK and STONE LINTEL SCHEDULE

	SPAN	36" HIGH	48" HIGH	LINTEL SIZE	WINDOW ABOVE
*BRICK	Up to 6'-0"	---	---	L3 1/2 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	---	L6 x 4 x 5/16	L7 x 4 x 5/16
	Up to 16'-3"	L7 x 4 x 3/8	L8 x 4 x 1/2	L8 x 4 x 1/2	**per Design
*STONE	Up to 6'-0"	---	---	L4 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	L6 x 4 x 5/16	L7 x 4 x 5/16	**per Design
	Up to 16'-3"	---	L8 x 4 x 1/2	**per Design	**per Design

All Lintels: 4" Minimum bearing required each end  
\* Brick is based on 40psf and Stone is based on 60psf  
\*\* Any lintels not described by the above parameters shall be specifically designed

\*\* Any lintels not described by the above parameters shall be

For more information, contact the author at [www.earthworks.org](http://www.earthworks.org).

**RESIDENCE FOR:**

KI FINMAN

# 3759 BENDEMEER ELEVATE

Job Number: DOYL-0201-00	Drawing Date: 09/24/25	Coord Name: LUKE RAMLER	Coord Phone: (859)-578-4212
House Name: the NORTHWOOD	Drawing Scale: 1/8" = 1'-0"		Series: SERIES I
			Plan No.:

## the NORTHWOOD

The logo for Drees Homes, featuring the word "drees" in a green, lowercase, sans-serif font with a small green square icon to the left, and "HOMES" in a smaller, uppercase, bold green font below it.

Sheet Information

6.01

**FRONT & REAR ELEVATIONS**

### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. REFER TO SELECTIONS/SPECIFICATIONS FOR ROOFING MATERIAL.
3. GARAGE DOOR PER SELECTIONS WITH SIDE ENTRY GARAGE OPTION

**TYPICAL TRIM:**  
6" FASCIA - 8" w/ HARDIE SOFFIT  
(ALL SIDES)  
8" FRIEZE  
(FRONT ONLY UNLESS OTHERWISE NOTED)

### Key Notes

- 1 --
- 2 --
- 3 --
- 4 --
- 5 --
- 6 --
- 7 --
- 8 --
- 9 --
- 10 --
- 11 --
- 12 --
- 13 --
- 14 --

### BRICK and STONE LINTEL SCHEDULE

	SPAN	36" HIGH	48" HIGH	LINTEL SIZE	WINDOW ABOVE
"BRICK	Up to 6'-0"	---	---	L3 1/2 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	---	L6 x 4 x 5/16	L7 x 4 x 3/8
	Up to 16'-3"	L7 x 4 x 3/8	L8 x 4 x 1/2	L8 x 4 x 1/2	**per Design
"STONE	Up to 6'-0"	---	---	L4 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	---	L6 x 4 x 5/16	L7 x 4 x 3/8
	Up to 16'-3"	---	---	L8 x 4 x 1/2	**per Design

All Lintels: 4" Minimum bearing required each end  
 \* Brick is based on 40psf and Stone is based on 60psf  
 \*\* Any lintels not described by the above parameters shall be specifically designed.

REISSUED: 10/10/25

RESIDENCE FOR:  
**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212

House Name:	Drawing Scale: 1/8" = 1'-0"	Series:
the NORTHWOOD		SERIES II

Plan No.:
-----------

<b>Drees</b> HOMES <sup>SM</sup>	6.02
Copyright © 2016, (2016) The Drees Company. All Rights Reserved. 6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141 PHONE: (440) 717-9670	SIDE ELEVATIONS ELEVATION "E"





TYPICAL TRIM:	
6" FASCIA - 8" w/ HARDIE SOFITT (ALL SIDES)	
8" FRIEZE (FRONT ONLY UNLESS OTHERWISE NOTED)	

#### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. REFER TO SELECTIONS/SPECIFICATIONS FOR ROOFING MATERIAL.

#### Key Notes

- 1 -
- 2 -
- 3 -
- 4 -
- 5 -
- 6 -
- 7 -
- 8 -
- 9 -
- 10 -
- 11 -
- 12 -
- 13 -
- 14 -

#### BRICK and STONE LINTEL SCHEDULE

	SPAN	36" HIGH	48" HIGH	LINTEL SIZE	WINDOW ABOVE
*BRICK	Up to 6'-0"	---	---	L3 1/2 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	---	L6 x 4 x 5/16	L7 x 4 x 3/8
	Up to 16'-3"	L7 x 4 x 3/8	L8 x 4 x 1/2	L8 x 4 x 1/2	**per Design
*STONE	Up to 6'-0"	---	---	L4 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/16	---
	Up to 9'-3"	---	L6 x 4 x 5/16	L7 x 4 x 3/8	**per Design
	Up to 16'-3"	---	L8 x 4 x 1/2	**per Design	**per Design

All Lintels: 4" Minimum bearing required each end  
 \* Brick is based on 40psf and Stone is based on 60psf  
 \*\* Any lintels not described by the above parameters shall be specifically designed.

#### RESIDENCE FOR:

**KLEINMAN**  
**3759 BENDMEER**  
**ELEVATE**

Job Number: DOYL-0201-00 Drawing Date: 09/24/25 Coord Name: LUKE RAMLER Coord Phone: (859)-578-4212

House Name: Drawing Scale: 1/8" = 1'-0" Series: SERIES II

the NORTHWOOD Plan No.:

**Drees**  
**HOMES** SM

Copyright © 2016, (2016) The Drees Company. All Rights Reserved.  
 6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141  
 PHONE: (440) 717-9670

Sheet Information

**6.03**  
 REAR ELEVATION  
 ELEVATION "E"

<b>TYPICAL TRIM:</b>	
6" FASCIA - 8" w/ HARDIE SOFITT (ALL SIDES)	
8" FRIEZE (FRONT ONLY UNLESS OTHERWISE NOTED)	

#### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. REFER TO SELECTIONS/SPECIFICATIONS FOR ROOFING MATERIAL.

#### Key Notes

- [1] --
- [2] --
- [3] --
- [4] --
- [5] --
- [6] --
- [7] --
- [8] --
- [9] --
- [10] --
- [11] --
- [12] --
- [13] --
- [14] --

#### BRICK and STONE LINTEL SCHEDULE

	SPAN	36" HIGH	48" HIGH	LINTEL SIZE	WINDOW ABOVE
*BRICK	Up to 6'-0"	---	---	L3 1/2 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/8	---
	Up to 9'-3"	---	---	L6 x 4 x 5/8	L7 x 4 x 3/8
	Up to 16'-3"	L7 x 4 x 3/8	L8 x 4 x 1/2	L8 x 4 x 1/2	**per Design
*STONE	Up to 6'-0"	---	---	L4 x 3 1/2 x 1/4	---
	Up to 8'-3"	---	---	L5 x 3 1/2 x 5/8	---
	Up to 9'-3"	---	L6 x 4 x 3/8	L7 x 4 x 3/8	**per Design
	Up to 16'-3"	---	L8 x 4 x 1/2	**per Design	**per Design

All Lintels: 4" Minimum bearing required each end  
 \* Brick is based on 40psf and Stone is based on 60psf  
 \*\* Any lintels not described by the above parameters shall be specifically designed.

**RESIDENCE FOR:**  
**KLEINMAN**  
**3759 BENDEMEER**  
**ELEVATE**

Job Number:	Drawing Date:	Coord Name:	Coord Phone:
DOYL-0201-00	09/24/25	LUKE RAMLER	(859)-578-4212

House Name:	Drawing Scale: 1/8" = 1'-0"	Series:
-------------	-----------------------------	---------


SERIES II

Plan No.:
-----------


the NORTHWOOD
---------------

 Copyright © 2016, [2016] The Drees Company. All Rights Reserved. 6860 W SNOWVILLE RD, SUITE 150, BRECKSVILLE, OH 44141 PHONE: (440) 717-9670	<b>6.04</b> SIDE ELEVATION ELEVATION "E"
---	--


Sheet Information










A BUILDING SECTION THROUGH STAIRS  
7.02 SCALE: 1/8" = 1'-0"



**FIRST TO SECOND FLOOR STAIR DETAIL**



# TRAY CEILING IN TRUSS SPACE



## General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.

## Key Notes

- 1 --
- 2 --
- 3 --
- 4 --
- 5 --
- 6 --
- 7 --
- 8 --
- 9 --
- 10 --
- 11 --
- 12 --
- 13 --
- 14 --
- 15 --
- 16 --
- 17 --
- 18 --
- 19 --
- 20 --

RESIDENCE FOR:  
KLEINMAN  
3759 BENDMEER  
ELEVATE

Job Number: DOYL-0201-00	Drawing Date: 09/24/25	Coord Name: LUKE RAMLER	Coord Phone: (859)-578-4212
House Name: the NORTHWOOD	Drawing Scale: 1/8" = 1'-0"		Series: SERIES II
			Plan No.:

## the NORTHWOOD

**drees**  
HOMES<sup>SM</sup>

Sheet Information

# 7.02

DETAILS  
ELEVATION "E"

CONNECTION SPECIFICATIONS (TYP. U.N.O.)	
NOTE: 10d NAIL = 3" x 0.13" GUN NAIL	
JOIST TO SOLE PLATE	(3)10d TOENAILS
SOLE PLATE TO JOIST/BLK'G.	10d NAILS @ 6" O.C.
STUD TO SOLE PLATE	(3)10d NAILS
TOP OR SOLE PLATE TO STUD	10d NAILS
RIM TO TOP PLATE	10d TOENAILS @ 6" O.C.
BLK'G. BTWN. JOISTS TO TOP PL.	(3)10d TOENAILS
RAFTER/TRUSS TO TOP PLATE	(3)10d TOENAILS + (1) SIMPSON H2.5A
GAB. END TRUSS TO DBL. TOP PL.	10d TOENAILS @ 8" O.C.
R.T. w/ HEEL HT. 9 1/4" TO 12"	2x10 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.
R.T. w/ HEEL HT. 12" TO 16"	2x12 BLK EVERY 3RD BAY FASTENED TO DBL. TOP PLATE w/ 10d TOENAILS @ 6" O.C.
R.T. w/ HEEL HT. UP TO 24"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN W/ 8d NAILS @ 6" O.C.
R.T. w/ HEEL HT. 24" TO 48"	LAP WALL SHTG. w/ DBL. TOP PL. & INSTALL ON TRUSS VERT. - FASTEN W/ 8d NAILS @ 6" O.C. PROVIDE 2x BLK & EA. BAY AT TOP OF HEEL
DOUBLE STUD	10d NAILS @ 24" O.C.
DOUBLE TOP PLATE	10d NAILS @ 24" O.C.
DOUBLE TOP PLATE LAP SPLICE	(10)10d NAILS IN LAPPED AREA
TOP PLATE LAP @ CORNERS & INTERSECTING WALLS	(2)10d NAILS
WALL TO FOUNDATION	WALL SHTG. LAP w/ SILL PL. & FASTENED PER SHEAR WALL FASTENING SPEC.

BASEMENT SLAB	
3,500 PSI 4" CONC. SLAB ON 6 MIL VAPOR BARRIER ON 4" MIN. GRANULAR FILL ON 95% COMPAKTED FILL/VIRGIN SOIL	
GARAGE SLAB	
3,500 PSI 4" CONC. SLAB w/ 6x6-W1.4 WNF ON 6 MIL VAPOR BARRIER ON 4" MIN. GRANULAR FILL ON 95% COMPAKTED FILL/VIRGIN SOIL	
EXTERIOR SLABS	
4,500 PSI 4" CONC. SLAB ON 95% COMPAKTED FILL/VIRGIN SOIL	

## STEEL CONNECTIONS CHART

CONNECTION TYPE	CONNECTION SPECIFICATION
TO STL. COLUMN (INTERIOR CONDITION)	CAP COLUMN TOP PLATE EITHER WELDED ALONG THE TWO SIDES PERPENDICULAR TO THE BEAM'S LENGTH OR BOLTED WITH (2) 1/2" DIAMETER BOLTS PLACED DIAGONALLY THROUGH THE TOP PLATE
	BASE ANCHORED TO CONCRETE FOOTING PAD WITH (2) 1/2" DIAMETER CONC. ANCHORS THROUGH THE STEEL BASE PLATE TO THE CONCRETE FOUNDATION. - OR - ENCASED IN CONCRETE SLAB
	CAP COLUMN TOP PLATE BOLTED TO BEAM WITH AT LEAST (4) 1/2" DIAMETER BOLTS
TO STL. COLUMN (END CONDITION)	BASE ANCHORED TO CONCRETE FOOTING PAD WITH (4) 1/2" DIAMETER CONC. ANCHORS THROUGH THE STEEL BASE PLATE TO THE CONCRETE FOUNDATION. - OR - ENCASED IN CONCRETE SLAB
	STEEL BM SUPPORTED ON WOOD FRAME BOTTOM FLANGE OF STEEL BEAM FASTENED TO SUPPORTING WOOD FRAMING w/ (2) 1/2" DIA. X 3 1/2" LONG LAG SCREWS.
	STEEL BEAM IN BEAM POCKET CLIP ANGLES EITHER WELDED TO THE BEAM ALONG EACH CLIP ANGLE'S ENTIRE LENGTH OR BOLTED TO THE BEAM USING A MINIMUM OF 1/2" DIAMETER BOLTS. CLIP ANGLE ATTACHED TO THE FOUNDATION WALL USING NO LESS THAN (1) 1/2" DIAMETER ANCHOR OR (2) 1/2" DIA. X 2 1/4" LONG TAPCON SCREWS. - OR - BEAM POCKET GROUTED SOLID AROUND STEEL BEAM

## 'LOOSE' VENEER LINTEL SCHEDULE

SPAN (MAX)	HEIGHT OF VENEER ABOVE LINTEL	STEEL ANGLE SIZE
3'-0"	20 FT. MAX	L4x3 1/4" -OR- L5x3 1/4"
6'-0"	3 FT. MAX	L4x3 1/4" -OR- L5x3 1/4"
8'-0"	12 FT. MAX	L5x3 1/4"
9'-6"	5 FT. MAX	L5x3 1/4"
12'-0"	2 FT. MAX	L5x3 1/4"

## BOLTED VENEER LINTEL SCHEDULE

HEIGHT OF VENEER ABOVE LINTEL	FASTENER SPACING
4 FT. MAX	1/2" DIA. X 3" LONG LAG
6 FT. MAX	3/8" DIA. X 4" LONG LAG
8 FT. MAX	1/2" DIA. X 4" LONG LAG
12 FT. MAX	1/2" DIA. X 4" LONG LAG

FOR VENEER HEIGHTS ABOVE OPENING BETWEEN 12'-20' PROVIDE L5x3 1/4" STEEL ANGLE FASTENED TO LVL HDR W/ 3/8" X 4" LAG SCREWS @ 4" O.C. -OR- 3/4" X 4" LAG SCREWS @ 6" O.C.  
BOLTED LINTEL PARAMETERS:  
- BOLTED LINTELS SHALL BE L5x3 1/4" STEEL ANGLES, U.N.O.  
- LINTELS SHALL ONLY BE FASTENED BACK TO HEADERS WHERE SPECIFICALLY NOTED ON PLAN.  
- ALL BOLTED LINTELS MUST BE FASTENED TO LVL HEADERS. SOLID SAWN OR L.SL ALTERNATES ARE NOT ACCEPTABLE.  
- SHALL SUPPORT 2 1/2" - 3 1/2" VENEER W/ 40 psf MAXIMUM HEIGHT.  
- MAX. VENEER HT. SHALL NOT EXCEED THE HIGHEST PORTION OF BRICK OVER THE OPENING.  
- ALL LINTELS SHALL BE LONG LEG VERTICAL.  
- ALL LINTELS SHALL BE MADE OF 36 KSI STEEL.  
- SEE STRUCTURAL PLANS FOR LVL HEADER SIZE.  
- FOR ANY CONDITIONS NOT CONTAINED WITHIN THE PARAMETERS OF THIS TABLE, CONSULT MK FOR FURTHER EVALUATION.

\* 1/2" SIMPSON SDS SCREWS ARE AN ACCEPTABLE ALTERNATIVE TO 1/2" DIA. LAG SCREWS

MK STND. - MAY 2016

## GENERAL STRUCTURAL NOTES

### FOUNDATION

- DESIGN IS BASED ON 2019 OHIO RESIDENTIAL CODE.
- FOOTING DESIGN - 1500 PSF NET ALLOWABLE SOIL BEARING PRESSURE IS ASSUMED. BUILDER/CONTRACTOR MUST VERIFY.
- FASTEN 2x SILL PLATES TO CONC FND WITH A MINIMUM OF 2 ANCHORS PER PLATE, 12" MAX. FROM PLATE ENDS - UTILIZING:
  - 1/2" DIA. ANCHOR BOLTS @ 6'-0" O.C., 7" MIN. EMBEDMENT
  - SIMPSON MAB STRAPS @ 32" O.C.
  - SIMPSON MASA ANCHOR STRAPS @ 6'-0" O.C.
- ALL LUMBER EXPOSED TO WEATHER OR IN CONTACT W/ PERIMETER FOUNDATION SHALL BE PRESERVATIVE TREATED SOUTHERN PINE #2.
- BUILDER TO VERIFY CORROSION-RESISTANCE COMPATIBILITY OF HARDWARE & FASTENERS IN CONTACT W/ PRESERVATIVE-TREATED WOOD. CONTACT LUMBER & HARDWARE SUPPLIERS TO COORD.
- FOUNDATION WALLS & FOOTINGS SHALL BE PLAIN CONCRETE, U.N.O.

- CONCRETE DESIGN BASED ON ACI 318. CONCRETE SHALL ATTAIN THE FOLLOWING MIN. COMPRESSIVE STRENGTHS IN 28 DAYS, U.N.O.:  
F'c = 3,000 psi: ..... FOUNDATION WALLS  
2,500 psi: ..... FOOTINGS  
f\_y = 60,000 psi

- BASEMENT FOUNDATION WALL DESIGN BASED ON:  
- 8" OR 9" HEIGHT (AS NOTED ON PLANS)  
- TALLER WALLS MUST BE ENGINEERED.  
- NOMINAL WIDTH (8" FOR 8" & 9" FOUNDATION WALLS).
- BASEMENT WALL DESIGN IS BASED ON A MAXIMUM 60 PCF BACKFILL SOIL TYPE CLASSIFICATION:  
- 60 PCF SOIL TYPE (SG, ML-CL, OR GL)  
- ALL BOLTED LINTELS SHALL BE CONTINUOUSLY SHEATHED AND ARE CONSIDERED SHEAR WALLS.
- BASEMENT WALLS SHALL BE BRADED, PRIOR TO BACKFILLING, BY ADEQUATE TEMPORARY BRAZING OR INSTALL 1st FLOOR DECK.

- PROVIDE (2) #5 BARS AROUND ALL SIDES OF OPENINGS IN CONCRETE BSMT. FND. WALL WITH 2" CLEAR. REINFORCEMENT SHALL EXTEND 12" PAST CORNER OF OPENING IN ALL DIRECTIONS.  
- FOR OPENINGS UP TO 36", PROVIDE MINIMUM 10" CONCRETE DEPTH OVER OPENING OR (3)2x10 w/(2)2x6 JACK STUDS, U.N.O.  
- LARGER OPENINGS SHALL BE PER PLAN.
- ALL CONCRETE EXPOSED TO THE WEATHER SHALL NOT HAVE LESS THAN 5% OR MORE THAN 1% AIR ENTRAINMENT.
- ALL FOOTINGS SHALL BEAR BELOW FROST LINE (TYP.) OR 12" MIN IN REGIONS WHERE CODE FROST DEPTH IS NOT APPLICABLE. CONSULT SOILS REPORT OR BUILDING DEPT. FOR MINIMUM DEPTH BELOW GRADE.
- FOOTINGS AND SLABS ON GRADE SHALL BEAR ON VIRGIN SOIL OR 95% COMPAKTED FILL.

- PROVIDE CONTROL JOINTS AT ALL INSIDE CORNERS OF SLAB EDGES, AND OTHER LOCATIONS WHERE SLAB CRACKS ARE LIKELY TO DEVELOP.  
- JOINTS SHALL BE LOCATED @ 10'-0" O.C. (RECOMMENDED) OR 15'-0" O.C. (MAXIMUM)  
- JOINT GRID PATTERN SHALL BE AS CLOSE TO SQUARES AS POSSIBLE (1:1 RATIO), WITH A MAXIMUM OF 1:15 RATIO  
- CONTROL JOINTS SHALL NOT BE INSTALLED IN STRUCTURAL SLABS
- TYPICAL REINFORCEMENT DETAILS: PROVIDE 3" MIN. CLEAR COVER WHERE CAST AGAINST REBAR, 1 1/2" MIN. CLEAR COVER AGAINST FORMS. LAP ALL REBAR 48 BAR DIAMETERS MIN. (24" FOR #4 BARS) & BEND BARS AND LAP AT CORNERS. PROVIDE 6" HOOK INTO SUPPORTING FOOTINGS WHEN FOOTINGS INTERSECT.
- DIMENSIONS BY OTHERS, BUILDER TO VERIFY.

MK STND. - MAY 2012

### LEGEND

- INTERIOR BEARING WALL
- BEARING WALL ABOVE
- BEAM / HEADER
- EXTENT OF OVERFRAMING
- METAL HANGER
- INDICATES EXTENT OF INT. OSB SHEARWALL, BLOCKED PANEL EDGES, AND/OR 3" O.C. EDGE NAILING
- INDICATES HOLDOWN
- INDICATES POST ABOVE (P.A.) PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.

## LATERAL/WALL BRACING & WALL SHEATHING SPECIFICATIONS

### GENERAL

- THIS MODEL HAS BEEN DESIGNED TO RESIST LATERAL FORCES RESULTING FROM:  
**115 MPH WIND IN 2019 RCO MAP**  
(115 MPH WIND SPEED  
IN ASCE 7 WIND MAP)  
EXP. B & SEISMIC CAT. A/B.

- THE DESIGN WAS COMPLETED PER 2024 OBC (SECTION 1604) & ASCE 7, AS PERMITTED BY R301.3 OF THE 2019 RCO. ACCORDINGLY, THIS MODEL, AS DOCUMENTED AND DETAILED HEREWITHIN, IS ADEQUATE TO RESIST THE CODE REQUIRED LATERAL FORCES, AND DOES NOT NEED TO CONFORM TO THE PRESCRIPTIVE PROVISIONS OF SECTION R602.10 WITHIN THE 2019 RCO.

### EXT. WALL SHEATHING SPECIFICATION

- 1/16" OSB OR 15/32" PLYWOOD:  
FASTEN SHEATHING W/ 2 3/8" X 0.13 NAILS @ 6" O.C. AT EDGES & 12" O.C. IN THE PANEL FIELD.

- ALL SHEATHING PANELS SHALL BE ORIENTED VERTICALLY (LONG DIRECTION PARALLEL TO STUDS) AND INSTALLED FULL HEIGHT OF SHEAR WALL - OR - 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT ALL UNSUPPORTED PANEL EDGES & EDGE FASTENING.
- ALL EXT. WALLS SHALL BE CONTINUOUSLY SHEATHED AND ARE CONSIDERED SHEAR WALLS.
- WITHIN 48" OF ALL ROOF EDGES, RIDGES, & HIPS FASTEN ROOF SHEATHING FEEDS PER EDGE NAILING SPEC.

### 3" O.C. EDGE NAILING

- AT DESIGNATED AREAS - FASTEN PANEL EDGES OF WOOD STRUCTURAL WALL SHEATHING TO FRAMING W/ 2 3/8" X 0.13 NAILS @ 3" O.C. AND 12" O.C. IN THE PANEL FIELD NO STAPLE ALTERNATIVE AVAILABLE AT THIS SPEC. ALL SHEATHING PANELS SHALL BE ORIENTED VERTICALLY (LONG DIRECTION PARALLEL TO STUD) AND INSTALLED FULL HEIGHT OF SHEAR WALL - OR - 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT UNSUPPORTED PANEL EDGES AND 3" O.C. EDGE FASTENING.
- NOTES
  - SEE CONNECTION SPECIFICATIONS CHART FOR STANDARD SHEAR TRANSFER DETAILING. IF ADDITIONAL CAPACITY IS REQUIRED BY DESIGN, IT WILL BE SPECIFICALLY NOTED ON PLAN.
  - DESIGN ASSUMES 16" O.C. MAX. STUD SPACING, U.N.O.
  - ALL STRUCTURAL PANELS ARE TO BE DIRECTLY APPLIED TO STUD FRAMING.
  - PRE-MANUFACTURED PANELIZED WALLS:  
FASTEN TOGETHER END STUDS OF WALL PANELS SHEATHED W/ OSB OR PLYWOOD W/ 10d NAILS @ 4" O.C. (THRU ONE SIDE ONLY)

MK STND. - MAR 2016

## GENERAL STRUCTURAL NOTES

### FLOOR FRAMING

- I-JOISTS/TRUSSES SHALL BE DESIGNED BY MANUF. TO MEET OR EXCEED L/480 LIVE LOAD DEFLECTION CRITERIA. (EXCLUDES STONE/MARBLE OR WET BED CONSTRUCTED FLOORS - CONTACT MK FOR EXCLUDED FLOOR DESIGNS)

- PER THE GUIDELINES OF THE TIE COUNCIL OF NORTH AMERICA (TCA) HANDBOOK, IT SHALL BE THE FLOOR FINISH INSTALLER'S RESPONSIBILITY TO VERIFY THAT THE FINISHES TO BE INSTALLED MATCH THE DESIGN CRITERIA NOTED ABOVE (UNDER "DESIGN LOADS").

- AT I-JOIST FLOORS, PROVIDE 1 1/8" MIN. OSB RIM BOARD.

- METAL HANGERS SHALL BE SPECIFIED BY MANUFACTURER, U.N.O.

- I-JOIST/TRUSS SHOP DINGS. SHALL BE SUBMITTED TO ARCH. & ENG. FOR REVIEW AND APPROVAL PRIOR TO FABRICATION OR DELIVERY.
- FLOOR SHEATHING SHALL BE 23/32" A.P.A. RATED 'STUD-FLOOR' 24" O.C. EXPOSURE 1 (OR APPROVED EQUAL) WITH TONGUE AND GROOVE EDGES. FASTEN TO FRAMING MEMBERS W/ GLUE AND - 2 1/2" X 0.13" NAILS @ 6" O.C. @ PANEL EDGES & @ 12" O.C. FIELD.


- 2 3/8" X 0.120" NAILS @ 4" O.C. @ PANEL EDGES & @ 8" O.C. FIELD.

- 2 3/8" X 0.113" NAILS @ 3" O.C. @ PANEL EDGES & @ 6" O.C. IN FIELD.




**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING

300 Brookside Ave, Building 4 • Ambler, PA 19002  
p 215-646-8001 • mulhernkulp.com



Mulhern+Kulp project number:

085-16008



**Drees** HOMES<sup>SM</sup>

Mulhern+Kulp project number:  
085-16008

project mgr: APV  
drawn by: JWK  
issue date: 10-6-2025

REVISIONS:  
date: initial:

**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING  
301 Braddock Ave, Building 4 • Andrewsville, PA 18822  
215-545-8800 • mulhernkulp.com

**LATERAL DETAILS**  
**NORTHWOOD**  
**DOYL-O201**  
OHIO

sheet:


**SD-1**



## GARAGE PORTAL FRAME BRACING ELEVATION

SCALE: N.T.S.

BOTH SIDES OF GARAGE DOOR  
115 MPH WIND SPEED (ULT)



SECTION A-A THROUGH PIER


NOTE: ALL SHEATHABLE AREAS OF EXTERIOR WALL SHALL BE FULLY SHEATHED WITH  $\frac{1}{2}$ " PLYWOOD OR  $\frac{3}{8}$ " OSB

WALL FRAMING SPECIFICATION:  
① 2x4 WALL: USE HF #2 GRADE STUDS (OR BETTER)  
② 2x6 WALL: USE SPF STUD GRADE STUDS (OR BETTER)

FASTEN TOP PLATE TO HEADER W/ 2 ROWS OF  $\frac{3}{8}$ " x 0.148" NAILS @ 3" O.C.  
SIMPSON STRAP SPEC BASED ON PONY WALL HEIGHT  
-MSTA44 STRAP w/ 24 1/2" END LENGTH FOR 2'-0" MAX HT.  
-MS1066 STRAP w/ 33" END LENGTH FOR 5'-0" MAX HT.  
-STRAP CENTERED @ BOTTOM OF HEADER  
-LOCATE ON INSIDE FACE OF WALL

PLAN VIEW OF CORNER DETAIL

ALTERNATIVES TO  $\frac{1}{2}$ " DIA. ANCHOR BOLT:  
1)  $\frac{1}{2}$ " DIA. x 6" LONG SIMPSON TITEN HD  
2)  $\frac{1}{2}$ " DIA. THREADED ROD EPOXY SET w/  $\frac{1}{4}$ " EMBED.  
(MIN UTILIZING HILTI HY200 EPOXY ANCHORING SYSTEM  
(OR EQUAL)



PLAN VIEW OF CORNER DETAIL

ALTERNATIVES TO  $\frac{1}{2}$ " DIA. ANCHOR BOLT:  
1)  $\frac{1}{2}$ " DIA. x 6" LONG SIMPSON TITEN HD  
2)  $\frac{1}{2}$ " DIA. THREADED ROD EPOXY SET w/  $\frac{1}{4}$ " EMBED.  
(MIN UTILIZING HILTI HY200 EPOXY ANCHORING SYSTEM  
(OR EQUAL)

BOTH SIDES OF GARAGE DOOR  
115 MPH WIND SPEED (ULT)

PONY WALL MAX. HT:  
-2'-0" w/ SIMPSON MSTA44  
-5'-0" w/ SIMPSON MS1066  
EXTENT OF HEADER  
3"x11 1/4" MIN. HEADER  
(SEE PLAN)  
LOCATE HEADER @ TOP OF OPENING  
FASTEN HEADER TO KING STUDS W/ (6)  $\frac{3}{8}$ " x 0.148" NAILS  
FASTEN SHEATHING TO HEADER WITH  $\frac{1}{2}$ " x 0.131" NAILS IN 3" GRID PATTERN AS SHOWN AND 3" O.C.  
IN ALL FRAMING STUDS & SILLS - TYPICAL, 3" O.C.  
NAILING ONLY REQ'D WHERE INDICATED BY X's - USE 5" STUD, 5" NAILING ELSEWHERE  
IF PANEL SPLICING IS NEEDED IT SHALL OCCUR WITHIN MIDDLE 24" OF WALL HEIGHT. PROVIDE 2x HORIZONTAL  
BLOCKING TO SUPPORT PANEL EDGES.  
MIN. PANEL WIDTH BASED ON  
6:1 HEIGHT-TO-WIDTH ASPECT RATIO  
FOR EXAMPLE: 16' MIN. FOR 8' HEIGHT  
MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.


MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.

MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.


MIN. (2) JACK STUDS OR AS  
NOTED ON PLAN  
ANCHOR BOLTS PER CODE (2 MIN.)  
WITH 2x2x3/8" PLATE WASHERS.




8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO

CONCRETE SPECIFICATION CHART		
SOIL TYPE (PCF)	WALL (PSI)	FOOTING (PSI)
60	*3000*	2500

1 8' FOUNDATION WALL DETAIL  
D1.1  
SCALE: 1/4" = 1'-0"






8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO



8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO

VERTICAL REBAR CHART		
SOIL TYPE (PCF)	REBAR	SPACING
60	#4 VERT.	@ 15" o.c.
	#5 VERT.	@ 22" o.c.
	#6 VERT.**	@ 31" o.c.

2 9' FOUNDATION WALL DETAIL  
D1.1  
SCALE: 1/4" = 1'-0"



8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO

VERTICAL REBAR CHART		
SOIL TYPE (PCF)	REBAR	SPACING
60	#4 VERT.	@ 15" o.c.
	#5 VERT.	@ 22" o.c.
	#6 VERT.**	@ 31" o.c.

3 8' FOUNDATION WALL DETAIL  
WITH DROPPED BRICK LEDGE  
D1.1  
SCALE: 1/4" = 1'-0"


Drees Homes  
6860 West Snowville Road, Suite 150, Brecksville, Ohio 44141 Ph: (440) 717-9670  
Copyright © 2019 The Drees Company. All rights reserved. These plans are protected by Copyright. No part of these plans may be reproduced in any form or by any means, including photocopying, without the written permission from the Copyright owner.





Std. By: ALL Sheet Description:  
Chk. By: ARC  
Std. Date: 5/22/09 MIDWEST REGION  
Date of Last Rev: 01/03/19 AKS OHIO FOUNDATION DETAILS - 2000 PSF (MIN.) SOIL BEARING  
g:\architecture\autocad 2004\symbols\details\general\mulhern and kulp engineering\basement foundation details.dwg 9.23.2019

DETAILS MAY NOT APPLY TO CONTRACT



Sheet No.  
D1.1





8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO





VERTICAL REBAR CHART		
SOIL TYPE (PCF)	REBAR	SPACING
60	#4 VERT.	@ 15" o.c.
	#5 VERT.	@ 22" o.c.
	#6 VERT.**	@ 31" o.c.

CONCRETE SPECIFICATION CHART		
SOIL TYPE (PCF)	WALL (PSI)	FOOTING (PSI)
60	*3000*	2500

1 8' FOUNDATION WALL DETAIL  
D1.1  
SCALE: 1/4" = 1'-0"

CONCRETE SPECIFICATION CHART		
SOIL TYPE (PCF)	WALL (PSI)	FOOTING (PSI)
60	*3000*	2500

2 9' FOUNDATION WALL DETAIL  
D1.1  
SCALE: 1/4" = 1'-0"



8" CONCRETE WALL  
ENGINEERED PER ACI 332-14  
AS PERMITTED BY SECTION  
404.1.3 OF THE 2019  
RESIDENTIAL CODE OF OHIO


VERTICAL REBAR CHART		
SOIL TYPE (PCF)	REBAR	SPACING
60	#4 VERT.	@ 15" o.c.
	#5 VERT.	@ 22" o.c.
	#6 VERT.**	@ 31" o.c.

CONCRETE SPECIFICATION CHART		
SOIL TYPE (PCF)	WALL (PSI)	FOOTING (PSI)
60	*3000*	2500



3 8' FOUNDATION WALL DETAIL  
WITH DROPPED BRICK LEDGE  
D1.1  
SCALE: 1/4" = 1'-0"


CONCRETE SPECIFICATION CHART		
SOIL TYPE (PCF)	WALL (PSI)	FOOTING (PSI)
60	*3000*	2500

4 9' FOUNDATION WALL DETAIL  
WITH DROPPED BRICK LEDGE  
D1.1  
SCALE: 1/4" = 1'-0"




31-MAY-2024






STEPPED FOUNDATION WALL DETAIL  
WITH WALKOUT BASEMENT

1 D1.2 SCALE: 1/4" = 1'-0"




STEPPED FOUNDATION WALL  
ANCHORAGE DETAIL

2 D1.2 SCALE: 1/2" = 1'-0"



TYPICAL FOUNDATION  
SIDE WALL DETAIL




3 D1.2 SCALE: 1/2" = 1'-0"



TYPICAL BASEMENT  
FOUNDATION WALL

4 D1.2 SCALE: 1" = 1'-0"





**WOOD WINDOW IN FOUNDATION**

D1.3

SCALE: 1/4" = 1'-0"

**FAUX STONE VENEER FLASHING DETAIL**


D1.3

SCALE: 1 1/2" = 1'-0"

**FAUX STONE VENEER FLASHING DETAIL**

D1.3

SCALE: 1 1/2" = 1'-0"



**FOUNDATION DROP @ GARAGE DOOR DETAIL**

D1.3

SCALE: 1/2" = 1'-0"

**STD. DETAIL SHEET**

REGION: **CLEVELAND**

Std. By: ALL  
Chk. By: ARC  
Std. Date: 10.11.06  
Date of Last Rev: 12/19/07 BRG


Sheet Description:  
**FOUNDATION DETAILS**

**DETAILS MAY NOT APPLY TO CONTRACT**



CLEVE - D-SHEETS.dwg Sep 07, 2022 - 8:47am

Sheet No.


**D1.3**



WALL PLAN



WALL ELEVATION



WALL ELEVATION DETAIL


**FOUNDATION WALL  
CONTROL JOINT DETAIL**  
A  
DI.4  
SCALE: 1/2" = 1'-0"

**General Notes**


1. REFER TO SHEET ON.1 FOR GENERAL NOTES.

**Key Notes**

- 1 --
- 2 --
- 3 --
- 4 --
- 5 --
- 6 --



PLAN VIEW




SECTION VIEW

FOUNDATION DOOR DETAIL


D1.5

SCALE: 1/2" = 1'-0"



NOTES:

- CAULK 2x6 FRAME TO FOUNDATION WALL PRIOR TO INSTALLING TAPE AND TRIM
- INSTALL TAPE ON SIDES AND THEN THE TOP
- INSTALL TRIM BOARDS AND CAULK



SECTION VIEW

FOUNDATION WINDOW DETAIL (W/ WOOD FORM BUCK)




















B  
D1.5

General Notes


1. REFER TO SHEET 0N.1 FOR GENERAL NOTES.

Key Notes

1 --  
2 --  
3 --  
4 --  
5 --  
6 --




Sheet No.  
D2.1




DETAIL


SCALE: 1/2" = 1'-0"




SECTION



ELEVATION




PLAN




SEAT DETAILS


SCALE: 1/8" = 1'-0"



③ FRAME WRAP RECESSED ENTRY




② BRICK WRAP RECESSED ENTRY



① NU-WOOD RECESSED ENTRY

RECESSED ENTRY DETAILS  
D2.3 SCALE: 1/4" = 1'-0"



E  
D2.3  
KITCHEN HALF WALL DETAIL  
SCALE: 1/2" = 1'-0"



6650 West Snowville Road, Suite J, Brecksville, Ohio 44141 Ph: (440) 717-9670  
Copyright ©, 2005 The Drees Company, All rights reserved. These plans are protected by Copyright.  
No part of these plans may be reproduced in any form or by any means, including photocopying,  
without the written permission from the Copyright owner.

Drees Homes

STD. DETAIL SHEET  
REGION: CLEVELAND








Std. By: ALL  
Chk. By: ARC  
Std. Date: 10.11.06  
Date of Last Rev: 12/19/07 BRG


Sheet Description:  
RECESSED ENTRY DETAILS  
DORMER DETAILS

DETAILS MAY NOT APPLY TO CONTRACT  
CLEVE - D-SHEETS.dwg Jun 10, 2015 - 10:15am

Sheet No.


D2.3






**MASONRY OVER ROOF DETAIL W/ COMMON FRAMING**

SCALE: 1/2" = 1'-0"




**ROOF FLASHING @ BRICK WALL**

SCALE: 1" = 1'-0"



**ROOF FLASHING @ BRICK WALL**

SCALE: 1" = 1'-0"



**MASONRY OVER ROOF DETAIL W/ TRUSSES**

SCALE: 1/2" = 1'-0"

**Drees**  
**HOMES**

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141 Ph: (440) 717-9670  
Copyright ©, 2005 The Drees Company, All rights reserved. These plans are protected by Copyright.  
No part of these plans may be reproduced in any form or by any means, including photocopying,  
without the written permission from the Copyright owner.

**STD. DETAIL SHEET**


REGION:  
**CLEVELAND**

Std. By: BDT  
Chk. By: ARC  
Std. Date: 05/08/07  
Date of Last Rev: 12/19/07 BRG

Sheet Description:  
**BRICK OVER ROOF DETAILS**

**DETAILS MAY NOT APPLY TO CONTRACT**  
CLEVE - D-SHEETS.dwg Jun 10, 2015 - 10:16am


Sheet No.  
**D2.7**



**DETAIL RECESSED FAKE SHUTTER IN BRICK**

B.8

SCALE: 1" = 1'0"




**PLAN**

**SECTION**

**FRONT PORCH BOX BEAM DETAIL**

D.8


SCALE: 1" = 1'0"



**CRAFTSMAN STYLE INTERIOR TRIM PACKAGE - ELEVATION**

E.8


## RETANGULAR TUB



RETANGULAR TUB PLAN

SCALE: 1/8" = 1'-0"


OPEN SIDE ELEVATION



RECTANGULAR DROP-IN TUB PANEL ELEVATIONS

SCALE: 1/2" = 1'-0"


## CORNER TUB



CORNER TUB PLAN



SCALE: 1/8" = 1'-0"

OPEN SIDE ELEVATION




CORNER DROP-IN TUB PANEL ELEVATIONS

SCALE: 1/2" = 1'-0"



SIDE ELEVATION w/ SHOWER




SECTION THRU REMOVABLE PANEL AT TUB PLATFORM

2-1/4" CASE MOULDING  
1/2" DURAPLY  
1/2" CONCRETE BOARD  
6x6 CERAMIC TILE  
1-1/4" PANEL CUTOUT  
1-1/4" 2x4 WOOD KNEE WALL  
FRAMING FOR DROP IN TUB.  
1-1/8" FRAME HEIGHT  
10 1/2" 1-1/4" BASE MOULDING


A) PANEL SECTION

PANEL SECTION DETAILS

SCALE: 1" = 1'-0"




B) PANEL BACK



### TUB DETAILS

SCALE: 1/8" = 1'-0"




### SHOWER DETAILS

SCALE: 1/8" = 1'-0"

### STD. OWNER'S BATH DETAILS (WITH SEPERATE SHOWER)

SCALE: 1/8" = 1'-0"




### JETTED TUB DETAILS

SCALE: 1/8" = 1'-0"


### JETTED OWNER'S BATH DETAILS

SCALE: 1/8" = 1'-0" (SHOWER UNITS SAME AS STD. BATH)



### TUB DETAILS (JETTED TUBS SAME DETAILS)

SCALE: 1/8" = 1'-0"




### SHOWER DETAILS

SCALE: 1/8" = 1'-0"


### DESIGNER OWNER'S BATH DETAILS

SCALE: 1/8" = 1'-0"



### HALL BATH (CONVENTIONAL TUB) DETAILS


SCALE: 1/8" = 1'-0"



### PED SINK DETAILS\*

SCALE: 1/8" = 1'-0"


\*(STD. IN POWDER ROOMS)



### VANITY DETAILS\*


SCALE: 1/8" = 1'-0"

\*(HALL BATH AND OWNER'S BATH ONLY)




### CORNER TUB DETAIL

SCALE: 1/8" = 1'-0"



**DETAILED SECTION**

SCALE: 1" = 1'-0"




**DETAILED SECTION**

SCALE: 1" = 1'-0"



**TYPICAL ROOM SECTION**


SCALE: 1/4" = 1'-0"



**TYPICAL PLAN LAYOUT**


SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.



**TYPICAL ROOM SECTION**

SCALE: 1/4" = 1'-0"



**TYPICAL PLAN LAYOUT**

SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.

Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-01" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	
Drawing3.dwg Jan 09, 2018 - 11:45am				

CL-01


Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-04" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	
Drawing3.dwg Jan 09, 2018 - 11:45am				

CL-04




DETAILED SECTION

SCALE: 1" = 1'-0"



TYPICAL ROOM SECTION


SCALE: 1/4" = 1'-0"



TYPICAL PLAN LAYOUT


SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.



TYPICAL ROOM SECTION

SCALE: 1/4" = 1'-0"



TYPICAL PLAN LAYOUT

SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.

Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-05" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	
Drawing3.dwg Jan 09, 2018 - 11:46am				

CL-05


Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-07" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED


DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	
Drawing3.dwg Jan 09, 2018 - 11:46am				

CL-07




DETAILED SECTION

SCALE: 1" = 1'-0"



TYPICAL ROOM SECTION


SCALE: 1/4" = 1'-0"



TYPICAL PLAN LAYOUT


SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.




DETAILED SECTION

SCALE: 1" = 1'-0"



TYPICAL ROOM SECTION

SCALE: 1/4" = 1'-0"



TYPICAL PLAN LAYOUT

SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.

Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-08" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	

CL-08

Drees Homes


6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-11" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	


CL-11

Drawing3.dwg Jan 09, 2018 - 11:46am




**DETAILED SECTION**

SCALE: 1" = 1'-0"



**TYPICAL ROOM SECTION**

SCALE: 1/4" = 1'-0"



**TYPICAL PLAN LAYOUT**

SCALE: 1/4" = 1'-0"

TYPICAL PLAN LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY. FOR DIMENSIONS THAT VARY, REFER TO HOUSE PLANS FOR SPECIFIC ROOM SIZES.

Drees Homes


6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

"CL-14" CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	08/27/13	DRAWN BY:	BLC	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	


Drawing3.dwg Jan 09, 2018 - 11:47am

**CL-14**



**DETAILED SECTION**

SCALE: 1" = 1'-0"



**TYPICAL PLAN LAYOUT**

SCALE: 1/4" = 1'-0"

Drees Homes

6650 West Snowville Road, Suite J, Brecksville, Ohio 44141

CEDAR BEAM CEILING DESIGN  
CLEVELAND  
SCALE: AS NOTED

DATE OF DETAIL:	XX/XX/XX	DRAWN BY:	XXXX	SHEET NO.
LAST REVISION:	XX/XX/XX	CHECKED BY:	XXXX	
DATE ISSUED:	XX/XX/XX	PLAN NUMBER:	XXXX	

Drawing3.dwg Jan 09, 2018 - 11:47am


**CEDAR**

### General Notes


1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. VERIFY FIREPLACE MODEL AND HEARTH SELECTION WITH CUSTOMER'S SELECTIONS.

### Key Notes

- 1 FUTURE FRAMING FOR F.P. OPENING AFTER INSULATION HAS BEEN INSTALLED IN EXT. WALLS
- 2 FLASHING
- 3 HEADER PER PLAN
- 4
- 5 1" AIRSPACE
- 6 BOX OUT FOR FLUE (REFER TO SELECTIONS FOR FIREPLACE AND OPENING HEIGHT)




FRAMEWRAP  
(SHOWN WITHOUT OPT. HEARTH)





FIREPLACE DOGHOUSE SECTIONS


SCALE: 1/4" = 1'-0"



DIRECT VENT REAR WALL FRAMING  
SCALE 1/4" = 1'-0"




FIREPLACE PLATFORM DETAIL  
SCALE: 1/2" = 1'-0"




FIREPLACE ROUGH OPENING SCHEDULE				
FIREPLACE MANUFACTURER	MODEL	A	B	C
		(FIREBOX REQUIRED WIDTH)	(FIREBOX REQUIRED HEIGHT) *ADD 18" W/ OPT. HEARTH	(FIREBOX REQUIRED DEPTH - INTERIOR REAR WALL TO FRONT EXTERIOR WALL)
HEAT & GLO	SLIMLINE SL-7	42"	38-1/4"	16-1/4"
	COSMO 42	49"	32-3/4" *RAISE 10" - SEE PLATFORM DETAIL*	17-3/4"
	NOVUS 33	39"	34-7/8"	19-5/8"
HEARTH & HOME	COURTYARD 36	42-1/2"	34-1/4"	20-1/4"
	COURTYARD 42	48-1/2"	34-1/4"	20-1/4"
	LANAI *NOT IN CINCY/NKY	57-3/4"	39-1/2"	17-5/8"
	RAVE 42	49"	32-3/4" *RAISE 15-1/4" - SEE PLATFORM DETAIL*	18-1/4"

all dimensions are in inches




## LEVEL- FULL HEIGHT

SCALE: 1/2" = 1'-0"




## SECTION – FULL HEIGHT

SCALE: 1/2" = 1'




## ELEVATION- HALF HEIGHT

SCALE: 1/2" = 1'



## SECTION - HALF HEIGHT

SCALE: 1/2" = 1'-0"



## PLAN VIEWS

SCALE: 1/2" = 1'-0"

FIREPLACE ROUGH OPENING SCHEDULE				
FIREPLACE MANUFACTURER	MODEL	A	B	C
		(FIREBOX REQUIRED WIDTH)	(FIREBOX REQUIRED HEIGHT)	(FIREBOX REQUIRED DEPTH - INTERIOR REAR WALL TO FRONT EXTERIOR WALL)
SCION	SCION 43"	45"	24-1/4"	7-5/8"
	SCION 55"	57"	24-1/4"	7-5/8"

# The Drees Company

## ELECTRIC FIREPLACE DETAIL

## MIDWEST REGION

SCALE: NONE

REVISED RV-


10

LAST REVISION

4.3.4.3.2.3.4

C:\Architecture\Cincinnati\Cinti Standard Drawings\Fireplace\Scion\_Fireplace\_Details.dwg - Jul. 15, 2024 - 10:29am

F-03



## PLAN VIEW


SCALE: 1/4" = 1'-0"

## GENERAL NOTES

1. THIS DETAIL TO BE USED ONLY WHEN OVERDIG EXCEEDS 2'-0"-  
FILL OVERDIG AREAS WITH GRAVEL IF LESS THAN 2'-0".
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. ALL REBAR SHALL BE  $F_y = 60$  KSI STEEL

#### ALTERNATE GARAGE SLAB


1. FILL OVERDIG COMPLETELY w/ SELF-COMPACTING GRAVEL FILL
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. SLAB REBAR OR GRADE BEAM NOT REQUIRED.
4. INSTALL SLAB KEYWAY PER DETAIL 3 THIS SHEET.




### KEYWAY DETAIL (ALL EDGES)

---

SCALE: 1/2" - 1





PLAN VIEW




SCALE: 1/4" = 1'-0"

GENERAL NOTES

1. THIS DETAIL TO BE USED ONLY WHEN OVERDIG EXCEEDS 2'-0". FILL OVERDIG AREAS WITH GRAVEL IF LESS THAN 2'-0".
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. ALL REBAR SHALL BE  $F_y = 60$  KSI STEEL


ALTERNATE GARAGE SLAB

1. FILL OVERDIG COMPLETELY w/ SELF-COMPACTING GRAVEL FILL.
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. SLAB REBAR OR GRADE BEAM NOT REQUIRED.
4. INSTALL SLAB KEYWAY PER DETAIL 3 THIS SHEET.





KEYWAY DETAIL (ALL EDGES)

SCALE: 1/2" = 1'-0"



MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING





## PLAN VIEW


SCALE: 1/4" = 1' 0"

## GENERAL NOTES

1. THIS DETAIL TO BE USED ONLY WHEN OVERDIG EXCEEDS 2'-0".  
FILL OVERDIG AREAS WITH GRAVEL IF LESS THAN 2'-0".
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. ALL REBAR SHALL BE  $F_y = 60$  KSI STEEL

ALTERNATE GARAGE SLAB

1. FILL OVERDIG COMPLETELY w/ SELF-COMPACTING GRAVEL FILL
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. SLAB REBAR OR GRADE BEAM NOT REQUIRED.
4. INSTALL SLAB KEYWAY PER DETAIL 3 THIS SHEET.



### KEYWAY DETAIL (ALL EDGES)

SCALE: 1/2" = 1' 0"



**LILHERN+KULP**  
STRUCTURAL ENGINEERS  
Ana. Design • ANNA, PA 15411  
800-448-4444 • [www.lk.com](http://www.lk.com)




10


#### GENERAL NOTES

1. THIS DETAIL TO BE USED ONLY WHEN OVERDIG EXCEEDS 2'-0". FILL OVERDIG AREAS WITH GRAVEL IF LESS THAN 2'-0".
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. ALL REBAR SHALL BE  $F_y = 60$  KSI STEEL

#### ALTERNATE GARAGE SLAB

1. FILL OVERDIG COMPLETELY w/ SELF-COMPACTING GRAVEL FILL.
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. SLAB REBAR OR GRADE BEAM NOT REQUIRED.
4. INSTALL SLAB KEYWAY PER DETAIL 3 THIS SHEET.





PLAN VIEW


SCALE: 1/4" = 1'-0"

GENERAL NOTES

1. THIS DETAIL TO BE USED ONLY WHEN OVERDIG EXCEEDS 2'-0". FILL OVERDIG AREAS WITH GRAVEL IF LESS THAN 2'-0".
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. ALL REBAR SHALL BE  $F_y = 60$  KSI STEEL


ALTERNATE GARAGE SLAB

1. FILL OVERDIG COMPLETELY w/ SELF-COMPACTING GRAVEL FILL.
2. CONCRETE STRENGTH AT SLAB: 3500 PSI
3. SLAB REBAR OR GRADE BEAM NOT REQUIRED.
4. INSTALL SLAB KEYWAY PER DETAIL 3 THIS SHEET.




SECTION THRU SLAB

SCALE: 1/4" = 1'-0"




SECTION THRU GRADE BEAM



SCALE: 1/4" = 1'-0"



KEYWAY DETAIL (ALL EDGES)



MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
www.mulhernkulp.com



## STRUCTURAL GARAGE SLAB HAUNCH AT BRICK LEDGE

SCALE: 3/4"=1'-0"



**MULHERN+KULP**  
RESIDENTIAL STRUCTURAL ENGINEERING

300 Brookside Ave, Building 4 ▷ Ambler, PA 19002  
p 215-646-8001 ▷ [mulhernkulp.com](http://mulhernkulp.com)

DREES HOMES

STRUCTURAL GARAGE SLAB  
HAUNCH AT BRICK LEDGE  
FOUNDATION WALL CONDITION

MIDWEST REGION

Mulhern+Kulp project number:	085-25000
project mgr:	APV
drawn by:	CNV
issue date:	05-14-2025
sketch no.:	SK-1




### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. DESIGN LOADS:  
DECK LOAD: 40 p.s.f. LIVE LOAD + 15 p.s.f. DEAD LOAD = 55 p.s.f. TOTAL LOAD  
ROOF LOAD: 25 p.s.f. LIVE LOAD + 20 p.s.f. DEAD LOAD = 45 p.s.f. TOTAL LOAD
3. ALL WOOD TO BE PRESSURE TREATED EXCEPT FOR TRIM, WHICH IS TO BE REDWOOD.
4. ALL DECK COLUMNS TO HAVE AN UNSUPPORTED LENGTH NO GREATER THAN 10'-0" OR, IF OVER 10'-0", TO BE REVIEWED BY ARCHITECTURE DEPARTMENT.
5. HOUSE WALL REMAINS BRICK AT SCREENED-IN DECK.
6. HOUSE WALL IS 8" V-GROOVE HARDBOARD SIDING AT SCREENED-IN DECK WITH 1x8 BASE TRIM AND 1x4 TRIM AT HARDBOARD SEAMS, WINDOWS AND DOOR.
7. PRE-ENGINEERED TRUSSES AT 24" O.C.
8. ALL 12" OVERHANGS TO HAVE (2) SOFFIT VENTS PER EACH 8'-0" SECTION OF SOFFIT
9. WHERE THERE IS NO SECOND FLOOR ABOVE, GRADUATED TRUSSES ARE REQUIRED ATOP HOUSE ROOF AT SCREENED-IN DECK TO FINISH OUT THE REVERSE GABLE.
10. SEE SHEET 4.01 FOR PLACEMENT OF ALL MECHANICAL ELEMENTS.
11. WHEN A POST ABUTS VINYL SIDING OR STONE VENEER, PLACE A 5/4 x 6 EXTERIOR TRIM BOARD VERTICALLY, IN LINE WITH THE POST TO ADHERE THE RAIL & SCREENED-IN SYSTEM TO THE VINYL SIDING OR STONE VENEER.


### Key Notes

- 1 CONTINUOUS (2)2x12 HEADER W/ 1/2" FILLER - TO BEAR IN HOUSE WALL
- 2 DROP PATIO FOUNDATION 4" BELOW TOP OF HOUSE FOUNDATION
- 3 FROST FOOTING AS REQUIRED BY GRADE
- 4
- 5
- 6 STUB STEEL REBAR OUT TOP OF FOUNDATION 2'-0" TO TIE INTO PATIO SLAB
- 7 #4 REBAR AT 24" O.C. IN BOTH DIRECTIONS
- 8 PROVIDE 5' OF RIDGE VENT
- 9 1x12 BOX HEADER
- 10
- 11 MANUFACTURED SCREEN SYSTEM AND DOOR TO BE INSTALLED BY OTHERS
- 12 SIMPSON TRUSS TIE H2.5A AT EACH TRUSS/BEAM CONNECTION
- 13
- 14 ATTACH 4x4 DIRECTLY TO WOOD FRAMING OF HOUSE THROUGH A) VINYL SIDING USING 5/8"x5" LAG BOLTS AT 24" O.C. -OR- B) BRICK VENEER USING 5/8"x10" LAG BOLTS AT 24" O.C.
- 15 USE SIMPSON AB44 FOR A 4x4 POST (AB46 FOR A 4x6 POST; AB66 FOR A 6x6 POST) AT EACH SIDE POST W/ 5/8"x6" LONG MASONRY ANCHOR BOLT AND WASHER BOLTED TO SLAB THROUGH CONTINUOUS (EXCEPT AT DOOR) PRESSURE TREATED 2x4 BOTTOM PLATE W/ KERF CUTS
- 16
- 17
- 18
- 19
- 20




**ROOF PLAN**

SCALE: 1/8" = 1'-0"




**PLAN LAYOUT**

SCALE: 1/8" = 1'-0"




**FOUNDATION PLAN**

SCALE: 1/8" = 1'-0"




**REAR ELEVATION**

SCALE: 1/8" = 1'-0"



**BUILDING SECTION**

SCALE: 1/8" = 1'-0"



**WALL SECTION**

SCALE: 1/2" = 1'-0"

HEEL CUT STANDARDS	
ROOF PITCH	HEEL CUT
4:12	3-3/4"
5:12	4-3/4"
6:12	5-3/4"
7:12	6-3/4"
8:12	7-3/4"
9:12	8-3/4"
10:12	9-3/4"
12:12	11-3/4"
14:12	1'-1-3/4"

### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. DESIGN LOADS:  
DECK LOAD: 40 p.s.f. LIVE LOAD + 10 p.s.f. DEAD LOAD = 50 p.s.f. TOTAL LOAD  
ROOF LOAD: SEE S-0
3. ALL WOOD TO BE PRESSURE TREATED.
4. ALL DECK COLUMNS TO HAVE AN UNSUPPORTED LENGTH NO GREATER THAN 10'-0" OR, IF OVER 10'-0", TO BE REVIEWED BY ARCHITECTURE DEPARTMENT.




### Key Notes

- 1 THIS SIDE OF DECK BUILT AGAINST HOUSE, USE A/D7.5 FOR STANDARD DECK CONNECTION. USE DETAILS SHEET D7.6 FOR BRICK TO GRADE DECK CONNECTION; USE DETAILS SHEET D7.7 FOR SIDING TO GRADE DECK CONNECTION
- 2 FLASHING AS REQUIRED
- 3 -
- 4 5/4x6 DECKING WITHOUT SPACING
- 5 1x4 DIAGONAL BRACING ATTACHED TO THE BOTTOM CHORD OF THE JOIST (NOT FLUSH).
- 6 JOIST AND SPACE PER PRINTS
- 7 WOOD POST- USE 6x6 POST UP TO 10'-0" IN HEIGHT MAXIMUM.
- 8 16" DIAMETER SONOTUBE FOOTING TO FROST, TYP.
- 9 USE SIMPSON ABW66Z FOR 6x6 POST
- 10 CONCRETE PAD
- 11 (2) ANGLE BRACKETS TO PREVENT KICKOUT
- 12 WOOD STEPS AS REQUIRED BY GRADE
- 13 2x2 @ 5-1/2 O.C.
- 14 5/4x6 RAIL CAP, GRASPABLE FINGER RECESS AREA SHOULD BE ON BOTH SIDES OF THE PROFILE. THE FINGER RECESS SHALL BEGIN WITHIN A DISTANCE OF 3/4 INCH MEASURED VERTICALLY FROM THE TALLEST PORTION OF THE PROFILE AND ACHIEVE A DEPTH OF AT LEAST 5/16 INCH WITHIN 7/8 INCH BELOW THE WIDEST PORTION OF THE PROFILE. THIS REQUIRED DEPTH SHALL CONTINUE FOR AT LEAST 3/8 INCH TO A LEVEL THAT IS NOT LESS THAN 1-3/4 INCHES BELOW THE TALLEST PORTION OF THE PROFILE. THE MINIMUM WIDTH OF THE HANDRAIL ABOVE THE RECESS SHALL BE 1-1/4 INCHES TO A MAXIMUM OF 2-3/4 INCHES. EDGES SHALL HAVE A MINIMUM RADIUS OF 0.01 INCH.
- 15 PRESSURE TREATED 4x4 POST
- 16 -
- 17 2x12 STAIR TREAD
- 18 ROUTED 2x10 STAIR STRINGER TO ACCEPT STAIR TREADS.
- 19 -
- 20 -
- 21 NOTCH TOP OF POST TO ACCEPT BEAM PER PRINTS - BOLT W/(2) 1/2" THROUGH BOLTS - DO NOT OVER CUT POST AT NOTCH - OR USE POST CAP PER PRINT
- 22 (2)2x12 P.T. DROPPED CANTD E.E.
- 23 2x BANDBOARD
- 24 -
- 25 2x4 RISER HELD TIGHT TO UNDERSIDE OF STAIR TREAD. ATTACH THROUGH ENDS AT STRINGER AND DOWN THROUGH TOP OF TREAD.


ALL MECHANICAL VENTS MUST BE HELD AT LEAST 12' FROM THE DECK

ISOMETRIC APPLICABLE FOR 10' MAX. DECK JOIST SPAN. SEE PLAN SPECIFIC NOTES FOR DECK JOIST SPANS OVER 10'

REFER TO CONTRACT FOR PLAN SPECIFIC INFORMATION



NOTCHED BEAM CONNECTION



POST CAP CONNECTION

POST AND BEAM CONNECTION

B-D7.5

### STANDARD DECK DETAILS

Sheet Description:

STANDARD WOOD DECK DETAIL

SCALE: VARIES

Sheet No.

D7.5






### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. DESIGN LOADS:  
DECK LOAD: 40 p.s.f. LIVE LOAD + 15 p.s.f. DEAD LOAD = 55 p.s.f. TOTAL LOAD  
ROOF LOAD: 25 p.s.f. LIVE LOAD + 20 p.s.f. DEAD LOAD = 45 p.s.f. TOTAL LOAD
3. ALL WOOD TO BE PRESSURE TREATED.
4. ALL DECK COLUMNS TO HAVE AN UNSUPPORTED LENGTH NO GREATER THAN 10'-0" OR, IF OVER 10'-0", TO BE REVIEWED BY ARCHITECTURE DEPARTMENT.

### Key Notes

- 1 -
- 2 -
- 3 -
- 4 -
- 5 -
- 6 -
- 7 -
- 8 -
- 9 -
- 10 -







### General Notes

1. REFER TO SHEET ON.1 FOR GENERAL NOTES.
2. DESIGN LOADS:  
DECK LOAD: 40 p.s.f. LIVE LOAD + 10 p.s.f. DEAD LOAD = 50 p.s.f. TOTAL LOAD  
ROOF LOAD: SEE S-0
3. ALL WOOD TO BE PRESSURE TREATED.
4. ALL DECK COLUMNS TO HAVE AN UNSUPPORTED LENGTH NO GREATER THAN 10'-0" OR, IF OVER 10'-0", TO BE REVIEWED BY ARCHITECTURE DEPARTMENT

### Key Notes

1. -
2. -
3. -
4. -
5. -
6. -
7. -
8. -
9. -
10. -








### General Notes


1. REFER TO SHEET ON.I FOR GENERAL NOTES.
2. DESIGN LOADS:  
DECK LOAD: 40 p.s.f. LIVE LOAD + 10 p.s.f. DEAD LOAD = 50 p.s.f. TOTAL LOAD  
ROOF LOAD: SEE S-9
3. ALL WOOD TO BE PRESSURE TREATED.
4. ALL DECK COLUMNS TO HAVE AN UNSUPPORTED LENGTH NO GREATER THAN 10'-0" OR, IF OVER 10'-0", TO BE REVIEWED BY ARCHITECTURE DEPARTMENT

### Key Notes

- 1 -
- 2 -
- 3 -
- 4 -
- 5 -
- 6 -
- 7 -
- 8 -
- 9 -
- 10 -



DECK ATTACHMENT DETAIL w/ CANTILEVERED JOISTS - SIDING  
B D7.9  
SCALE: 1" = 1'-0"



# Midwest Region Window Schedule

JELD-WEN Brickmould Vinyl 1500 Series				Ply Gem 1500 Vinyl Series				Andersen 100-Series				Andersen 200-Series				Andersen 400-Series				Pella Architect Classic Clad Wood Series			
Drees Callout	Designation	Rough Opening	Egress = "Y"	Drees Callout	Designation	Rough Opening	Egress = "Y"	Drees Callout	Designation	Rough Opening	Egress = "Y"	Drees Callout	Designation	Rough Opening	Egress = "Y"	Drees Callout	Designation	Rough Opening	Egress = "Y"	Drees Callout	Designation	Rough Opening	Egress = "Y"
SINGLE or DOUBLE HUNG																							
1640 S/H	BBMVST1848	1' - 6" x 4' - 0"		1640 S/H	1640	1' - 6" x 4' - 0"		1640 S/H	1640	1' - 6" x 4' - 0"		1640 S/H	244DH1840	1' - 8" x 4' - 0"		1640 S/H	TW18310	1' - 10 1/8" x 4' - 0 7/8"		1640 S/H	2147	1' - 9 3/4" x 3' - 11 3/4"	
1650 S/H	BBMVST1860	1' - 6" x 5' - 0"		1650 S/H	1650	1' - 6" x 5' - 0"		1650 S/H	1650	1' - 6" x 5' - 0"		1650 S/H	244DH1850	1' - 8" x 5' - 0"		1650 S/H	TW18410	1' - 10 1/8" x 5' - 0 7/8"		1650 S/H	2159	1' - 9 3/4" x 4' - 11 3/4"	
1660 S/H	BBMVST1872	1' - 6" x 6' - 0"		1660 S/H	1660	1' - 6" x 6' - 0"		1660 S/H	1660	1' - 6" x 6' - 0"		1660 S/H	244DH1860	1' - 8" x 6' - 0"		1660 S/H	TW18510	1' - 10 1/8" x 6' - 0 7/8"		1660 S/H	2171	1' - 9 3/4" x 5' - 11 3/4"	
1840 S/H	BBMVST1848	1' - 6" x 4' - 0"		1840 S/H	1840	1' - 8" x 4' - 0"		1840 S/H	1640	1' - 6" x 4' - 0"		1840 S/H	244DH1840	1' - 8" x 4' - 0"		1840 S/H	TW18310	1' - 10 1/8" x 4' - 0 7/8"		1840 S/H	2147	1' - 9 3/4" x 3' - 11 3/4"	
1850 S/H	BBMVST1860	1' - 6" x 5' - 0"		1850 S/H	1850	1' - 8" x 5' - 0"		1850 S/H	1650	1' - 6" x 5' - 0"		1850 S/H	244DH1850	1' - 8" x 5' - 0"		1850 S/H	TW18410	1' - 10 1/8" x 5' - 0 7/8"		1850 S/H	2159	1' - 9 3/4" x 4' - 11 3/4"	
1860 S/H	BBMVST1872	1' - 6" x 6' - 0"		1860 S/H	1860	1' - 8" x 6' - 0"		1860 S/H	1660	1' - 6" x 6' - 0"		1860 S/H	244DH1860	1' - 8" x 6' - 0"		1860 S/H	TW18510	1' - 10 1/8" x 6' - 0 7/8"		1860 S/H	2171	1' - 9 3/4" x 5' - 11 3/4"	
2030 S/H	BBMVST2436	2' - 0" x 3' - 0"		2030 S/H	2030	2' - 0" x 3' - 0"		2030 S/H	2030	2' - 0" x 3' - 0"		2030 S/H	244DH2030	2' - 0" x 3' - 0"		2030 S/H	TW20210	2' - 2 1/8" x 3' - 0 7/8"		2030 S/H	2535	2' - 1 3/4" x 2' - 11 3/4"	
2036 S/H	BBMVST2442	2' - 0" x 3' - 6"		2036 S/H	2036	2' - 0" x 3' - 6"		2036 S/H	2036	2' - 0" x 3' - 6"		2036 S/H	244DH2036	2' - 0" x 3' - 6"		2036 S/H	TW2036	2' - 2 1/8" x 3' - 8 7/8"		2036 S/H	2541	2' - 1 3/4" x 3' - 5 3/4"	
2040 S/H	BBMVST2448	2' - 0" x 4' - 0"		2040 S/H	2040	2' - 0" x 4' - 0"		2040 S/H	2040	2' - 0" x 4' - 0"		2040 S/H	244DH2040	2' - 0" x 4' - 0"		2040 S/H	TW20310	2' - 2 1/8" x 4' - 0 7/8"		2040 S/H	2547	2' - 1 3/4" x 3' - 11 3/4"	
2044 S/H	BBMVST2454	2' - 0" x 4' - 6"		2044 S/H	2044	2' - 0" x 4' - 6"		2044 S/H	2044	2' - 0" x 4' - 6"		2044 S/H	244DH2044	2' - 0" x 4' - 6"		2044 S/H	TW2042	2' - 2 1/8" x 4' - 4 7/8"		2044 S/H	2553	2' - 1 3/4" x 4' - 5 3/4"	
2046 S/H	BBMVST2454	2' - 0" x 4' - 6"		2046 S/H	2046	2' - 0" x 4' - 6"		2046 S/H	2046	2' - 0" x 4' - 6"		2046 S/H	244DH2046	2' - 0" x 4' - 6"		2046 S/H	TW2046	2' - 2 1/8" x 4' - 8 7/8"		2046 S/H	2553	2' - 1 3/4" x 4' - 5 3/4"	
2050 S/H	BBMVST2460	2' - 0" x 5' - 0"		2050 S/H	2050	2' - 0" x 5' - 0"		2050 S/H	2050	2' - 0" x 5' - 0"		2050 S/H	244DH2050	2' - 0" x 5' - 0"		2050 S/H	TW20410	2' - 2 1/8" x 5' - 0 7/8"		2050 S/H	2559	2' - 1 3/4" x 4' - 11 3/4"	
2060 S/H	BBMVST2472	2' - 0" x 6' - 0"		2060 S/H	2060	2' - 0" x 6' - 0"		2060 S/H	2060	2' - 0" x 6' - 0"		2060 S/H	244DH2060	2' - 0" x 6' - 0"		2060 S/H	TW20510	2' - 2 1/8" x 6' - 0 7/8"		2060 S/H	2571	2' - 1 3/4" x 5' - 11 3/4"	
2070 S/H	BBMVST2484	2' - 0" x 7' - 0"		2070 S/H	2070	2' - 0" x 7' - 0"		2070 S/H	2070	2' - 0" x 7' - 0"		2070 S/H	N/A	2' - 0" x 7' - 0"		2070 S/H	TW2072	2' - 2 1/8" x 7' - 4 7/8"		2070 S/H	2584	2' - 1 3/4" x 7' - 0 3/4"	
2440 S/H	BBMVST2848	2' - 4" x 4' - 0"		2440 S/H	2440	2' - 4" x 4' - 0"		2440 S/H	2640	2' - 6" x 4' - 0"		2440 S/H	244DH2440	2' - 4" x 4' - 0"		2440 S/H	TW24310	2' - 6 1/8" x 4' - 0 7/8"		2440 S/H	2947	2' - 5 3/4" x 3' - 11 3/4"	
2446 S/H	BBMVST2854	2' - 4" x 4' - 6"		2446 S/H	2446	2' - 4" x 4' - 6"		2446 S/H	2646	2' - 6" x 4' - 6"		2446 S/H	244DH2446	2' - 4" x 4' - 6"		2446 S/H	TW2446	2' - 6 1/8" x 4' - 8 7/8"		2446 S/H	2953	2' - 5 3/4" x 4' - 5 3/4"	
2450 S/H	BBMVST2860	2' - 4" x 5' - 0"		2450 S/H	2450	2' - 4" x 5' - 0"		2450 S/H	2650	2' - 6" x 5' - 0"		2450 S/H	244DH2460	2' - 4" x 6' - 0"		2450 S/H	TW24410	2' - 6 1/8" x 5' - 0 7/8"		2450 S/H	2959	2' - 5 3/4" x 4' - 11 3/4"	
2460 S/H	BBMVST2872	2' - 4" x 6' - 0"		2460 S/H	2460	2' - 4" x 6' - 0"		2460 S/H	2660	2' - 6" x 6' - 0"		2460 S/H	N/A	2' - 4" x 7' - 0"		2460 S/H	TW24510	2' - 6 1/8" x 6' - 0 7/8"		2460 S/H	2971	2' - 5 3/4" x 5' - 11 3/4"	
2470 S/H	BBMVST2884	2' - 4" x 7' - 0"	Y	2470 S/H	2470	2' - 4" x 7' - 0"	Y	2470 S/H	2670	2' - 6" x 7' - 0"		2470 S/H	244DH2640	2' - 6" x 4' - 0"		2470 S/H	TW2472	2' - 6 1/8" x 7' - 4 7/8"		2470 S/H	2984	2' - 5 3/4" x 4' - 0 3/4"	Y
2640 S/H	BBMVST3048	2' - 6" x 4' - 0"		2640 S/H	2640	2' - 6" x 4' - 0"		2640 S/H	2640	2' - 6" x 4' - 0"		2640 S/H	244DH2644	2' - 6" x 4' - 0"		2640 S/H	TW26310	2' - 8 1/8" x 4' - 0 7/8"		2640 S/H	2947	2' - 5 3/4" x 3' - 11 3/4"	
2644 S/H	BBMVST3054	2' - 6" x 4' - 6"		2644 S/H	2644	2' - 6" x 4' - 6"		2644 S/H	2646	2' - 6" x 4' - 6"		2644 S/H	244DH2646	2' - 6" x 4' - 6"		2644 S/H	TW2642	2' - 8 1/8" x 4' - 4 7/8"		2644 S/H	2953	2' - 5 3/4" x 4' - 5 3/4"	
2646 S/H	BBMVST3054	2' - 6" x 4' - 6"		2646 S/H	2646	2' - 6" x 4' - 6"		2646 S/H	2646	2' - 6" x 4' - 6"		2646 S/H	244DH2450	2' - 4" x 5' - 0"		2646 S/H	TW26410	2' - 8 1/8" x 5' - 0 7/8"		2646 S/H	2959	2' - 5 3/4" x 4' - 11 3/4"	
2650 S/H	BBMVST3060	2' - 6" x 5' - 0"		2650 S/H	2650	2' - 6" x 5' - 0"		2650 S/H	2650	2' - 6" x 5' - 0"		2650 S/H	244DH2450	2' - 4" x 5' - 0"		2650 S/H	TW26510	2' - 8 1/8" x 6' - 0 7/8"	Y	2660 S/H	2971	2' - 5 3/4" x 5' - 11 3/4"	
2660 S/H	BBMVST30																						

# Midwest Region Window Schedule

JELD-WEN Brickmould Vinyl 1500 Series			Ply Gem 1500 Vinyl Series			Andersen 100-Series			Andersen 200-Series			Andersen 400-Series			Pella Architect Classic Clad Wood Series		
Drees Callout	Designation	Rough Opening	Drees Callout	Designation	Rough Opening	Drees Callout	Designation	Rough Opening	Drees Callout	Designation	Rough Opening	Drees Callout	Designation	Rough Opening	Drees Callout	Designation	Rough Opening
FIXED or TRANSOM			FIXED or TRANSOM			FIXED or TRANSOM			FIXED or TRANSOM			FIXED or TRANSOM			FIXED or TRANSOM		
1620 FIXED	BBMVFW1823	1' - 6" x 2' - 0"	1620 FIXED	1- 6 x2-0	1' - 6" x 2' - 0"	1620 FIXED	1620	1' - 6" x 2' - 0"	1620 FIXED	244FX1820	1' - 8" x 2' - 0"	1620 FIXED	TWT18111	1' - 10 1/8" x 2' - 1 13/16"	1620 FIXED	1725	1' - 5 3/4" x 2' - 1 3/4"
1626 FIXED	BBMVFW1829	1' - 6" x 2' - 6"	1626 FIXED	1- 6 x2-6	1' - 6" x 2' - 6"	1626 FIXED	1626	1' - 6" x 2' - 6"	1626 FIXED	N/A	1' - 8" x 2' - 6"	1626 FIXED	TWT1827	1' - 10 1/8" x 2' - 9 13/16"	1626 FIXED	1732	1' - 5 3/4" x 2' - 8 3/4"
1630 FIXED	BBMVFW1835	1' - 6" x 3' - 0"	1630 FIXED	1- 6 x3-0	1' - 6" x 3' - 0"	1630 FIXED	1630	1' - 6" x 3' - 0"	1630 FIXED	244FX3016**	1' - 6" x 3' - 0"	1630 FIXED	TWT1831	1' - 10 1/8" x 3' - 3 13/16"	1630 FIXED	1735	1' - 5 3/4" x 2' - 11 3/4"
1634 FIXED	BBMVFW1840	1' - 6" x 3' - 5"	1634 FIXED	1- 6 x3-4	1' - 6" x 3' - 4"	1634 FIXED	1636	1' - 6" x 3' - 6"	1634 FIXED	244FX3416**	1' - 6" x 3' - 4"	1634 FIXED	Custom TWT1837	1' - 9 13/16" x 3' - 10 1/8"	1634 FIXED	1741	1' - 5 3/4" x 3' - 5 3/4"
1640 FIXED	BBMVFW1847	1' - 6" x 4' - 0"	1640 FIXED	1- 6 x4-0	1' - 6" x 4' - 0"	1640 FIXED	1640	1' - 6" x 4' - 0"	1640 FIXED	N/A	1' - 8" x 4' - 0"	1640 FIXED	Custom DHP18310	1' - 10 3/16" x 4' - 0 7/8"	1640 FIXED	1747	1' - 5 3/4" x 3' - 11 3/4"
1644 FIXED	BBMVFW1852	1' - 6" x 4' - 5"	1644 FIXED	1- 6 x4-4	1' - 6" x 4' - 4"	1644 FIXED	1646	1' - 6" x 4' - 6"	1644 FIXED	244FX4416**	1' - 6" x 4' - 4"	1644 FIXED	Custom DHP1837	1' - 10 3/16" x 4' - 0 7/8"	1644 FIXED	1753	1' - 5 3/4" x 4' - 5 3/4"
1650 FIXED	BBMVFW1859	1' - 6" x 5' - 0"	1650 FIXED	1- 6 x5-0	1' - 6" x 5' - 0"	1650 FIXED	1650	1' - 6" x 5' - 0"	1650 FIXED	N/A	1' - 8" x 5' - 0"	1650 FIXED	Custom DHP18410	1' - 10 3/16" x 5' - 0 7/8"	1650 FIXED	1759	1' - 5 3/4" x 4' - 11 3/4"
1810 FIXED	BBMVFW2011	1' - 8" x 1' - 0"	1810 FIXED	1- 8 x1-0	1' - 8" x 1' - 0"	1810 FIXED	1610	1' - 6" x 1' - 0"	1810 FIXED	244FX1810	1' - 8" x 1' - 0"	1810 FIXED	TWT1810	1' - 10 1/8" x 1' - 0 1/2"	1810 FIXED	2114	1' - 9 3/4" x 1' - 2 3/4"
1816 FIXED	BBMVFW2017	1' - 8" x 1' - 6"	1816 FIXED	1- 8 x1-6	1' - 8" x 1' - 6"	1816 FIXED	1616	1' - 6" x 1' - 6"	1816 FIXED	244FX1816	1' - 8" x 1' - 6"	1816 FIXED	TWT1815	1' - 10 1/8" x 1' - 7 13/16"	1816 FIXED	2117	1' - 9 3/4" x 1' - 5 3/4"
1818 FIXED	BBMVFW2017	1' - 8" x 1' - 6"	1818 FIXED	1- 8 x1-8	1' - 8" x 1' - 8"	1818 FIXED	1616	1' - 6" x 1' - 6"	1818 FIXED	N/A	1' - 8" x 1' - 8"	1818 FIXED	TWT1815	1' - 10 1/8" x 1' - 7 9 3/4"	1818 FIXED	2121	1' - 9 3/4" x 1' - 9 3/4"
1820 FIXED	BBMVFW2023	1' - 8" x 2' - 0"	1820 FIXED	1- 8 x2-0	1' - 8" x 2' - 0"	1820 FIXED	1620	1' - 6" x 2' - 0"	1820 FIXED	244FX1820	1' - 8" x 2' - 0"	1820 FIXED	TWT18111	1' - 10 1/8" x 2' - 1 13/16"	1820 FIXED	2125	1' - 9 3/4" x 2' - 1 3/4"
1834 FIXED	BBMVFW2040	1' - 8" x 3' - 5"	1834 FIXED	1- 8 x3-4	1' - 8" x 3' - 4"	1834 FIXED	1636	1' - 6" x 3' - 6"	1834 FIXED	244FX3416**	1' - 6" x 3' - 4"	1834 FIXED	Custom TWT1837	1' - 9 13/16" x 3' - 10 1/8"	1834 FIXED	2141	1' - 9 3/4" x 3' - 5 3/4"
1836 FIXED	BBMVFW2040	1' - 8" x 3' - 5"	1836 FIXED	1- 8 x3-6	1' - 8" x 3' - 6"	1836 FIXED	1636	1' - 6" x 3' - 6"	1836 FIXED	244FX3416**	1' - 6" x 3' - 4"	1836 FIXED	Custom TWT1837	1' - 10 1/8" x 3' - 9 13/16"	1836 FIXED	2141	1' - 9 3/4" x 3' - 5 3/4"
1840 FIXED	BBMVFW2047	1' - 8" x 4' - 0"	1840 FIXED	1- 8 x4-0	1' - 8" x 4' - 0"	1840 FIXED	1640	1' - 6" x 4' - 0"	1840 FIXED	N/A	1' - 8" x 4' - 0"	1840 FIXED	Custom DHP18310	1' - 10 3/16" x 4' - 0 7/8"	1840 FIXED	2147	1' - 9 3/4" x 3' - 5 3/4"
1844 FIXED	BBMVFW2053	1' - 8" x 4' - 6"	1844 FIXED	1- 8 x4-4	1' - 8" x 4' - 4"	1844 FIXED	1646	1' - 6" x 4' - 6"	1844 FIXED	244FX4416**	1' - 6" x 4' - 4"	1844 FIXED	Custom DHP1837	1' - 10 3/16" x 4' - 0 7/8"	1844 FIXED	2153	1' - 9 3/4" x 4' - 5 3/4"
1850 FIXED	BBMVFW2059	1' - 8" x 5' - 0"	1850 FIXED	1- 8 x5-0	1' - 8" x 5' - 0"	1850 FIXED	1650	1' - 6" x 5' - 0"	1850 FIXED	N/A	1' - 8" x 5' - 0"	1850 FIXED	Custom DHP18410	1' - 10 3/16" x 5' - 0 7/8"	1850 FIXED	2159	1' - 9 3/4" x 4' - 11 3/4"
1856 FIXED	BBMVFW2065	1' - 8" x 5' - 6"	1856 FIXED	1- 8 x5-6	1' - 8" x 5' - 6"	1856 FIXED	1656	1' - 6" x 5' - 6"	1856 FIXED	N/A	1' - 8" x 5' - 6"	1856 FIXED	Custom DHP1856	1' - 10 3/16" x 5' - 8 7/8"	1856 FIXED	2165	1' - 9 3/4" x 5' - 5 3/4"
2016 FIXED	BBMVFW2417	2' - 0" x 1' - 6"	2016 FIXED	2- 0 x1-6	2' - 0" x 1' - 6"	2016 FIXED	2016	2' - 0" x 1' - 6"	2016 FIXED	244FX2016	2' - 0" x 1' - 6"	2016 FIXED	TWT2015	2' - 2 1/8" x 1' - 7 13/16"	2016 FIXED	2317	1' - 11 3/4" x 1' - 5 3/4"
2018 FIXED	BBMVFW2417	2' - 0" x 1' - 6"	2018 FIXED	2- 0 x1-8	2' - 0" x 1' - 8"	2018 FIXED	2016	2' - 0" x 1' - 8"	2018 FIXED	244FX1820**	2' - 0" x 1' - 8"	2018 FIXED	TWT2015	2' - 2 1/8" x 1' - 7 13/16"	2018 FIXED	2317	1' - 11 3/4" x 1' - 5 3/4"
2020 FIXED	BBMVFW2423	2' - 0" x 2' - 0"	2020 FIXED	2- 0 x2-0	2' - 0" x 2' - 0"	2020 FIXED	2020	2' - 0" x 2' - 0"	2020 FIXED	244FX2020	2' - 0" x 2' - 0"	2020 FIXED	TWT20111	2' - 2 1/8" x 2' - 1 13/16"	2020 FIXED	2323	1' - 11 3/4" x 1' - 11 3/4"
2026 FIXED	BBMVFW2429	2' - 0" x 2' - 6"	2026 FIXED	2- 0 x2-6	2' - 0" x 2' - 6"	2026 FIXED	2026	2' - 0" x 2' - 6"	2026 FIXED	244FX2820**	2' - 0" x 2' - 8"	2026 FIXED	TWT2027	2' - 2 1/8" x 2' - 9 13/16"	2026 FIXED	2332	1' - 11 3/4" x 2' - 8 3/4"
2028 FIXED	BBMVFW2429	2' - 0" x 2' - 6"	2028 FIXED	2- 0 x2-8	2' - 0" x 2' - 8"	2028 FIXED	2026	2' - 0" x 2' - 6"	2028 FIXED	244FX2820**	2' - 0" x 2' - 8"	2028 FIXED	TWT2027	2' - 2 1/8" x 2' - 9 13/16"	2028 FIXED	2332	1' - 11 3/4" x 2' - 8 3/4"
2030 FIXED	BBMVFW2435	2' - 0" x 3' - 0"	2030 FIXED	2- 0 x3-0	2' - 0" x 3' - 0"	2030 FIXED	2030	2' - 0" x 3' - 0"	2030 FIXED	244FX3020**	2' - 0" x 3' - 0"	2030 FIXED	TWT2031	2' - 2 1/8" x 3' - 3 13/16"	2030 FIXED	2335	1' - 11 3/4" x 2' - 11 3/4"
2034 FIXED	BBMVFW2440	2' - 0" x 3' - 5"	2034 FIXED	2- 0 x3-4	2' - 0" x 3' - 4"	2034 FIXED	2036	2' - 0" x 3' - 6"	2034 FIXED	244FX3420**	2' - 0" x 3' - 4"	2034 FIXED	Custom TWT1837	2' - 2 1/8" x 3' - 9 13/16"	2034 FIXED	2341	1' - 11 3/4" x 3' - 5 3/4"
2036 FIXED	BBMVFW2440	2' - 0" x 3' - 5"	2036 FIXED	2- 0 x3-6	2' - 0" x 3' - 6"	2036 FIXED	2036	2' - 0" x 3' - 6"	2036 FIXED	N/A	2' - 0" x 3' - 6"	2036 FIXED	Custom TWT1837	2' - 2 1/8" x 3' - 9 13/16"	2036 FIXED	2341	1' - 11 3/4" x 3' - 5 3/4"
2040 FIXED	BBMVFW2447	2' - 0" x 4' - 0"	2040 FIXED	2- 0 x4-0	2' - 0" x 4' - 0"	2040 FIXED	2040	2' - 0" x 4' - 0"	2040 FIXED	N/A	2' - 0" x 4' - 0"	2040 FIXED	Custom DHP20310	2' - 2 1/8" x 4' - 0 7/8"	2040 FIXED	2347	1' - 11 3/4" x 3' - 11 3/4"
2050 FIXED	BBMVFW2459	2' - 0" x 5' - 0"	2050 FIXED	2- 0 x5-0	2' - 0" x 5' - 0"	2											

# MOULDED MILLWORK SCHEDULE

LAST REVISED 11/22/17

HEADERS			PILASTERS			MOULDINGS		
Drees General Callout	Nuwood	Fypon	Drees General Callout	Nuwood	Fypon	Drees General Callout	Nuwood	Fypon
ARCHED HEADER D1	H8xxEFR	N/A	FLUTED PILASTER A1	PL7xxF	PIL7XXX	BAND MOULD D1	M210-16	MLD612-12
ARCHED HEADER D1K	H8xxEFKR	N/A	FLUTED PILASTER B1	PL9xxF	PIL9XXX	BAND MOULD D2	M301-16	MLD220-16
ARCHED HEADER D2	H8xxEFTR	N/A	FLUTED PILASTER C1	PL11xxFM	PIL11XXX	BARGE MOULD D1	WM210	WM210
ARCHED HEADER D2K	H8xxEFTKR	N/A	PANEL PILASTER A2	PL7xxP	PIL7XXXDP	CASE MOULD D1	M320-16	MLD226-16
ARCHED HEADER D3	AH10xx	WCHSEGxxX10	PANEL PILASTER B2	PL9xxP	PIL9XXXDP	CASE MOULD D2	N/A	MLD244-12
ARCHED HEADER D3K	N/A	WCHSEGxxX10K	PANEL PILASTER C2	PL11xxPM	PIL11XXXDP	CROWN MOULD D1	M404-16	MLD572-16
ARCHED HEADER D4	AR5xx	ARxxX6M	PILASTER D1	M311-9	PIL10XXXA	DENTIL MOULD D1	M105-16	MLD310-16
ARCHED HEADER D4K	AR5xxK	ARxxX6MK	PILASTER D2	M323-9	N/A	DENTIL MOULD D2	M108-8	MLD353-8
ARCHED HEADER D5	AR10xxEC	ARxxX6METAR6C	PILASTER Z-E1-PIL	Z-E1-PIL	Z-E1-PIL	HALF ROUND MOULD D1	N/A	MLD605-12
ARCHED HEADER D5K	AR10xxECK	ARxxX6METAR6CK	PILASTER Z-E2-PIL	Z-E2-PIL	Z-E2-PIL	PANEL MOULD D1	M310-8 OR 16	MLD612-12
ARCHED HEADER D6	AR10xxC	ARxxX10MC	PILASTER Z-E3-PIL	Z-E3-PIL	Z-E3-PIL			
ARCHED HEADER D6K	AR10xxCK	ARxxX10MCK	PILASTER Z-PIL-EXT	Z-PIL-EXT	Z-PIL-EXT			
ARCHED HEADER D7K	H7xxEF-4K	N/A	PLAIN PILASTER A3	PL7xxS	PIL7XXXP			
ARCHED HEADER D8	AR14xxC	ARxxX14MC	PLAIN PILASTER B3	PL9xxS	PIL9XXXP			
ARCHED HEADER D8K	AR14xxCK	ARxxX14MCK	PLAIN PILASTER C3	PL11xxS	PIL11XXXP			
ARCHED HEADER D9	H9xxE	WCHARSxx13	PLINTH D1	PF10	ADD "P" TO END OF PILASTER			
CROSSHEAD A1	H9xx	WCHxxX9N	PLINTH D2	P14.5	N/A			
CROSSHEAD A1K	H9xxK	WCHxxX9NK	LOUVERS					
CROSSHEAD B1	H14xxBT	WCHxxX14BT	Drees General Callout	Nuwood	Fypon	PEDIMENTS / COMBO HEADERS		
CROSSHEAD B1K	H14xxBTK	WCHxxX14BTK	CATHEDRAL LOUVER D1	CLV1224	CLV12X24	Drees General Callout	Nuwood	Fypon
CROSSHEAD B2	H12xx	WCHxxX12	CATHEDRAL LOUVER D1T	CLV1224TRIM4	CLV12X24X4F	BROW COMBO D1	BCxx	CSAPxx
CROSSHEAD B2K	H12xxK	WCHxxX12K	CATHEDRAL LOUVER D2	CLV1432	CLV14X32	PEAK PEDIMENT D1	Pxx-4 (6:12)	PCPx
CROSSHEAD C1	H18xxBT	WCHxxX14BT	CATHEDRAL LOUVER D2T	CLV1432TRIM4	CLV14X32X4F	PEAK PEDIMENT Z-E1-PED	Z-E1-PED	Z-E1-PED
CROSSHEAD C1K	H18xxBTK	WCHxxX14BTK	CATHEDRAL LOUVER D3	CLV2232	CLV22X32	PEAKED COMBO D1	PCxx-4	CPCPx
CROSSHEAD C2	H18xxBT-PA	LDCHxxX18	CATHEDRAL LOUVER D3T	CLV2232TRIM4	CLV22X32X4F	RAMS HEAD PEDIMENT D1	Rxx	RHPxxOO
CROSSHEAD C2K	H18xxBTK-PA	LDCHxxX18K	HALF CIRCLE LOUVER D1	HRLV32	HRLV32X16	ROUND PEDIMENT D1	Bxx-4	PSPxx
CROSSHEAD Z-E1-HDR	Z-E1-HDR	Z-E1-HDR	HALF CIRCLE LOUVER D1T	HRLV32TRIM4	HRLV32X4F	SUNRISE COMBO D1	SCxx-4	CSPxx
CROSSHEAD Z-E2-HDR	Z-E2-HDR	Z-E2-HDR	HALF CIRCLE LOUVER D2	HRLV36	HRLV36X18	VICTORIAN PEDIMENT D1	VPxx	DVPxx w/ SWDHxxXxx
CROSSHEAD Z-E3-HDR	Z-E3-HDR	Z-E3-HDR	HALF CIRCLE LOUVER D2T	HRLV36TRIM4	HRLV36X4F			
CROSSHEAD Z-E3-ARCHHDR	Z-E3-ARCHHDR	Z-E3-ARCHHDR	OCTAGONAL LOUVER D1	OLV24	OLV24			
CROSSHEAD Z-E3-CLHDR	Z-E3-CLHDR	Z-E3-CLHDR	OCTAGONAL LOUVER D12	OLV24TRIM4	OLV24X4F			
CROSSHEAD Z-E5-HDR	Z-E5-HDR	Z-E5-HDR	OVAL LOUVER D1	OLV2537	OLV37X25			
WINDOW HEADER A1	H6xx	WCHxxX6	OVAL LOUVER D1T	OLV2537TRIM4	OLV37X25X4F			
WINDOW HEADER A1K	H6xxK	WCHxxX6K	RECTANGULAR LOUVER D1	LV1224V	LV12X24			
WINDOW HEADER B1	H9xx-2	WCHxxX9N	RECTANGULAR LOUVER D1T	LV1224VTRIM4	LV12X24-4F			
WINDOW HEADER B1K	H9xx-2K	WCHxxX9NK	RECTANGULAR LOUVER D2	LV1636V	LV16X36			
WINDOW HEADER B2	H9xxBT	WCHxxX10NBT	RECTANGULAR LOUVER D2T	LV1636VTRIM4	LV16X36-4F			
WINDOW HEADER B2K	H9xxBTK	WCHxxX10NBTK	RECTANGULAR LOUVER D3	LV2436V	LV24X36			
WINDOW HEADER C1	H9xx	CCAxXX10	RECTANGULAR LOUVER D3T	LV2436VTRIM4	LV24X36-4F			
WINDOW HEADER C1K	H9xxK	CCAxXX10K	RECTANGULAR LOUVER D4	LV2424V	LV24X24			
WINDOW HEADER C2	H9xxT	WCHxxX9T	RECTANGULAR LOUVER D4T	LV2424VTRIM4	LV24X24-4F			
WINDOW HEADER C2K	H9xxTK	WCHxxX9TK	ROUND LOUVER D1	RLV18	RLV18			
WINDOW HEADER C3	H12xxBT	WCHxxX10BT	ROUND LOUVER D1T	RLV18TRIM4	RLV18X4F			
WINDOW HEADER C3K	H12xxBTK	WCHxxX10BTK	ROUND LOUVER D2	RLV22	RLV22			
WINDOW HEADER C4	H14xxBT	WCHxxX14BT	ROUND LOUVER D2T	RLV22TRIM4	RLV22X4F			
WINDOW HEADER D1	H7xxF-4	N/A	TRIANGULAR LOUVER D1	--	TRLVxxx36			
WINDOW HEADER D1K	H7xxF-4K	N/A			00 47 0x0x			
WINDOW HEADER D2K	H9xxK-1	N/A						
WINDOW HEADER Z-W1	Z-W1	Z-W1	BRACKETS					
WINDOW HEADER Z-W3	Z-W3	Z-W3	Drees General Callout	Nuwood	Fypon			
WINDOW HEADER Z-W3K	Z-W3K	Z-W3K	EXTERIOR BRACKET D1	BR437	N/A			
WINDOW HEADER Z-W3D	Z-W3D	Z-W3D	EXTERIOR BRACKET D2	DB102	DTLB6X4X6			
WINDOW HEADER Z-W4	Z-W4	Z-W4	EXTERIOR BRACKET D3	BR304 (7" WIDE)	BKT24X24X7			
WINDOW HEADER Z-W4K	Z-W4K	Z-W4K	EXTERIOR BRACKET D4	BR455	N/A			
			EXTERIOR BRACKET D5	BR300-1	BKT12X12X6			
			EXTERIOR BRACKET D6	BR300	BKT12X12			
			EXTERIOR BRACKET D7	BR409	BKT16X18X3			
			EXTERIOR BRACKET D8	BR413	DTLB5X5X3			
			EXTERIOR BRACKET D9	TBD	BKT11X20			
			EXTERIOR BRACKET D10	TBD	BKT12X24X3			
			EXTERIOR BRACKET D11	BR435	BKT25X27			
			EXTERIOR BRACKET D12	BR404	BKT16X30X4			
			GABLE BRACKET D1	TBD	DTLB6X4X6R(OR L)PITCH			
			GABLE BRACKET D2	BR423-x:12	BKT5X20			
			GABLE BRACKET D3	BR424-x:12	BKT5X20 (CUT 2" PROJECTION)			

~~3755 Bendemeer Rd~~

Google Maps

3749 left across street





Image capture: Jul 2022 © 2025 Google



3749 Bendemeer Rd

Google Maps

3750 Bendemeer Right Adjacent Property





Image capture: Jul 2022 © 2025 Google



~~3756 Bendemeer Rd~~

Google Maps

3755 Bendemeer Across Street





Image capture: Jul 2022 © 2025 Google



3756 Bendemeer Rd

Google Maps

Subject Property





Image capture: Jul 2022 © 2025 Google



3761 Bendemeer Rd

Google Maps

Left Adjacent Property





Image capture: Jul 2022 © 2025 Google



Google Maps

3761 Bendemeer Rd  
3761 Right Side Across Street




Image capture: Jul 2022 © 2025 Google

